

<b>Section</b>	<b>Pages</b>	<b>Section</b>	<b>Pages</b>	<b>Section</b>	<b>Pages</b>
Hose	15-67	Swivel Joints	229-244	Quick Disconnect Couplings	268-345
Fittings	68-180	Flexmaster Joints	245-260	Access., Equipment & Assembly Instructions	346-393
Adapters and Tube Fittings	181-228	FLOCS®	261-267	Technical Data	394-433

# HOSE

## Alphabetical index

Description	Page	Description	Page	Description	Page
<b>Assembly Instructions</b>	362-376	MatchMate Plus®	24, 28-29, 33	Polyon™/Thermoplastic	57-62
<b>AQP Hose</b>	16-17	Single wire braid	22-25, 38, 43-44	Power steering	49
<b>Hose</b>	16-67	Textile braid	20-22	Railroad air brake	49
<b>Hydraulic</b>	19-38	Wire inserted suction	19-20	Refrigeration/Air conditioning	54-56
AQP®	19, 21-23, 27, 35-36	<b>Special application</b>	38-67	Safety Blow Gun	42
AQP/HI-IMPULSE®	22-24	Air brake	45-46, 50	Sewer cleaning	62-63
AQP/HI-PAC®	26	AQP®	40, 43, 45-47	Silicone rubber (coolant)	52
Double wire braid	27-30, 32, 39	Convuluted PTFE	63-64	Silicone rubber (heater)	51
Four heavy spiral wire	32-36	Engine and air brake	45-46	SOCKETLESS™	40-41
Four or six spiral wire	34-37	EPDM	38-39	PTFE	63-67
HI-IMPULSE®	22-24, 27-29, 32	Fuel and oil	45-46	Textile braid low pressure	40-41
HI-PAC®	26	Jack Hose	53	<b>How to order</b>	18
MatchMate Blue®	23, 27	LPG	47		
MatchMate Ice®	31	Polyon recoil air assemblies	42		

## Part number index

Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
302A	44	2556	41	2781	28	FC195	27	FC321	47	FC372	57	FC498	21
303	44	2565	41	2807	65	FC211	24	FC323	35	FC373	57	FC505	56
1503	43	2570	50	2808	67	FC212	29	FC324	36	FC374	58	FC510	26
1529	30	2575	41	CR170	48	FC234	45	FC325	36	FC375	58	FC555	55
1531	49	2580	21	FB9218	42	FC252	51	FC332	40	FC376	59	FC558	54
1531A	49	2583	22	FB9219	42	FC254	34	FC350	46	FC377	59	FC563	64
1540	55	2651	44	FB9220	42	FC273	35	FC352	52	FC414	48	FC579	53
2550	50	2661	19	FC136	33	FC300	43	FC355	45	FC465	66	FC606	37
2554	50	2681	23	FC186	65	FC310	26	FC363	63	FC466	20	FC611	38
2555	49	2766	30	FC194	22	FC318	20	FC364	64	FC469	67	FC616	53
												FC619	19
												FC636	39
												FC639	31
												FC645	66
												FC647	40
												FC650	46
												FC659	34
												FC690	60
												FC693	39
												FC699	47
												FC701	62
												FC702	63
												FC735	32
												FC736	32
												FC802	54
												FC901	61
												FC902	60
												FC914	61
												FC916	62
												FF9791	42
												GH120	31
												GH134	56
												GH194	23
												GH195	27
												GH466	38
												GH493	33
												GH506	37
												GH663	24
												GH681	25
												GH683	25
												GH781	28
												GH793	29

Flexible hose lines offer many advantages over rigid tubing including routing ease, vibration absorption, sound deadening and the ability to accommodate movement of connected components. However, hose lines require caution in use not only to provide long service but also to guard against potentially dangerous failure.

### Important

The user should carefully observe the precautions listed in this catalog, including the recommendations on the selection of hose and fittings (pages 395-396) and the pages on fluid compatibility (pages 400-404). In addition, care should be taken not to exceed the minimum bend radius listed for each hose size and type in the hose section. Maximum operating pressure should not exceed pressures listed in the hose data. Instructions for assembling fittings to different hoses should be followed carefully to ensure the performance of the completed assembly.

**WARNING:** Aeroquip fitting tolerances are engineered to match Aeroquip hose tolerances. The use of Aeroquip fittings on hose supplied by other manufacturers and/or the use of Aeroquip hose with fittings supplied by other manufacturers may result in the production of unreliable and unsafe hose assemblies and is neither recommended nor authorized by Aeroquip.

**WARNING:** Application considerations must be observed in selecting appropriate components for the application of these products contained herein. The failure to follow the recommendations set forth in this catalog may result in an unstable application which may result in serious personal injury or property damage.

**AEROQUIP SHALL NOT BE SUBJECT TO AND DISCLAIMS ANY OBLIGATIONS OR LIABILITIES (INCLUDING BUT NOT LIMITED TO ALL CONSEQUENTIAL, INCIDENTAL AND CONTINGENT DAMAGES) ARISING OUT OF BREACH OF CONTRACT OR OF WARRANTY OR ARISING FROM TORT CLAIMS (INCLUDING WITHOUT LIMITATION NEGLIGENCE AND STRICT LIABILITY) OR OTHER THEORIES OF LAW WITH RESPECT TO ANY HOSE ASSEMBLIES NOT PRODUCED FROM GENUINE AEROQUIP HOSE FITTINGS, HOSE AND AEROQUIP APPROVED EQUIPMENT, AND IN CONFORMANCE WITH AEROQUIP PROCESS AND PRODUCT INSTRUCTIONS FOR EACH SPECIFIC HOSE ASSEMBLY.**

Failure to follow Aeroquip process and product instructions and limitations could lead to premature hose assembly failures resulting in property damage, serious injury or death.

### Routing

If the user will follow the recommendations on hose line routing and installation on page 409, improved safety and longer service life of any hose installation will result.



The Aeroquip problem-solving family of AQP® hose featuring the patented\* AQP elastomer with temperatures up to +300°F

\*Patent Number 4,366,746



#### FC300 AQP HOSE

Exceeds SAE100R5

The superior high temperature, abrasion resistant hose. Features extensive fluid compatibility. See page 43.



#### FC194 AQP/Hi-IMPULSE HOSE

Exceeds SAE100R1A

Combines superior high temperature resistance and extensive fluid compatibility plus operating pressures up to 40% greater than SAE100R1 hose. Aeroquip **Hi-IMPULSE** hose construction is a patented process. Patent number 3,725,167. See page 22.



#### FC195 AQP/Hi-IMPULSE HOSE

Exceeds SAE100R2A

Combines superior high temperature resistance and extensive fluid compatibility plus operating pressures up to 40% greater than SAE100R2 hose. Aeroquip **Hi-IMPULSE** hose construction is a patented process. See page 27.



#### FC510 AQP/Hi-Pac HOSE

Exceeds SAE100R2

#### Performance Requirements

Combines the flexibility and economy of Hi-Pac hose with the temperature and fluid compatibility of AQP hose. Aeroquip Hi-Pac hose construction is patented. Patent number 3,463,197. See page 26.



#### FC323 AQP HOSE

Uniform Pressure

Spiral Wire Hose

3000 psi

The features of AQP construction and spiral wire reinforcement are combined in this quality hose style. See page 35.



#### FC324 AQP HOSE

Uniform Pressure

Spiral Wire Hose

4000 psi

Features the patented AQP tube compound and 4-spiral wire reinforcement. Uses the same fittings as FC323. See page 36.



#### FC325 AQP HOSE

Uniform Pressure

Spiral Wire Hose

5000 psi

Features the patented AQP tube compound and 4-spiral wire reinforcement. Pressures to 5000 psi. See page 36.



## The scientifically superior hose



### FC350 AQP HOSE

Exceeds FMVSS-106 Type All  
The revolutionary truck hose with superior abrasion resistance. Features an AQP tube for excellent fluid compatibility and temperature requirements. See page 46.



### FC355 AQP HOSE

Exceeds FMVSS-106 Type All  
Ideal for truck maintenance and piping conditions where fluid compatibility and chemical resistance are required. Has a blue AQP elastomer cover for fluid resistance. See page 45.



### FC234 AQP HOSE

Fire resistant fuel hose meets USCG A1 requirements. Offers positive fire resistance in critical applications without using a firesleeve. See page 45.



### FC332 AQP SOCKETLESS HOSE

Offers extended fluid compatibility and operating temperature range for low pressure applications. Used with Aeroquip *SOCKETLESS* fittings for quick and easy assembly. See page 40.



### FC498 AQP HOSE

Exceeds SAE100R6  
For low pressure applications. See page 21.



### 2661 AQP HOSE

Exceeds SAE100R4  
The dual-purpose hose with extensive fluid compatibility is ideal for either suction or chemical transfer applications. See page 19.



### GH194 MatchMate BLUE AQP/Hi-IMPULSE HOSE

Exceeds SAE 100R1AT  
A thin cover, 1-wire version of AQP/Hi-IMPULSE Hose that allows the use of Aeroquip's MatchMate Plus Thru-The-Cover (TTC) fittings. Pressures to 3250 psi. See page 23.



### GH195 MatchMate BLUE AQP/Hi-IMPULSE HOSE

Exceeds SAE 100R2AT  
A thin cover, 2-wire version of AQP/Hi-IMPULSE Hose that allows the use of Aeroquip's MatchMate Plus Thru-The-Cover (TTC) fittings. Pressures to 5750 psi. See page 27.



### FC650 AQP HOSE

High Temperature Fuel and Oil  
The revolutionary truck hose with superior abrasion resistance. Features an AQP tube for excellent fluid compatibility and temperature requirements. Pressure to 1000 psi. See page 46.



## How to Order

Accurate processing and prompt delivery of your order depend on easy identification of your requirements. Please order Aeroquip parts using correct part numbers as described in this catalog. Inquiries and orders should be directed to your Aeroquip Distributor or:

**Eaton Aeroquip**  
Industrial Division  
3000 Strayer Road, P.O. Box 631  
Maumee, Ohio 43537-0631  
419/867-2600; Fax: 419/867-2629  
www.aeroquip.com

### Part numbers and dash sizes

Dash size designates the nominal size in 16ths of an inch. This number immediately follows the part number and is separated from it with a dash.

### Dimensions

Dimensions given in this catalog for Aeroquip products are approximate and should be used for reference only. Exact dimensional information for a given product is subject to change and varying tolerances; contact Aeroquip directly for full current information.

### Hose assemblies

Aeroquip manufactures the terminal ends of our hose fittings to the appropriate requirements established by the SAE. Therefore, the performance ratings of these hose fittings meet the SAE requirements. It is possible to order a hose assembly with a fitting terminal end that has a performance rating lower than the hose rating. When ordering hose assemblies, please keep the connecting end performance rating in mind since this may affect overall hose assembly performance.

Hose assembly components (hose and fittings) are easily assembled in the field. However, factory assembled reusable and crimped hose assemblies are available. For complete information, contact Aeroquip.

### Cut length hose

Cut lengths of hose should be ordered as shown below by specifying lengths in inches.

For numeric part numbers: 2651- 10- 00484  
 Hose type \_\_\_\_\_  
 Hose size (in 16ths of an inch) \_\_\_\_\_  
 Cut length (in inches) \_\_\_\_\_  
 last digit is in 1/8ths of an inch 00484 = 48 1/2 inches

For alpha-numeric part numbers: FC300- 08- 00484  
 Hose type \_\_\_\_\_  
 Hose dash size \_\_\_\_\_  
 Cut length (in inches) \_\_\_\_\_  
 last digit is in 1/8ths of an inch 00484 = 48 1/2 inches

### Bulk hose

Bulk hose should be ordered by specifying length in feet as shown below.

Complete number 500 ft.- 2651- 10  
 Quantity (in feet) \_\_\_\_\_  
 Hose type \_\_\_\_\_  
 Hose size (in 16ths of an inch) \_\_\_\_\_

Note: Length tolerance for hose, assemblies and sleeves is:  
 Up to and including 12 inches:  $\pm 1/8$ "  
 Above 12 inches to and including 18 inches:  $\pm 3/16$ "  
 Above 18 inches to and including 36 inches:  $\pm 1/4$ "  
 Above 36 inches:  $\pm 1\%$  of length

**2661**

**Wire inserted suction**  
**Exceeds SAE 100R4**



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
2661-12	.75	1.25	300†	1200	5.00	28	.42	-40 Crimp	143
2661-16	1.00	1.50	250†	1000	6.00	28	.50	<b>Global</b>	
2661-20	1.25	1.80	200†	800	8.00	28	.90	Skive Nipples	74
2661-24	1.50	2.06	150†	600	10.00	28	1.13	OTC	74
2661-32	2.00	2.55	100†	400	12.00	28	1.30	TTC	74
2661-40	2.50	3.08	62	250	14.00	28	1.72	TTC12 (-12 only)	74
2661-48‡	3.00	3.58	56	225	18.00	28	1.96	<b>Sockets</b>	72
2661-64‡	4.00	4.69	50	200	24.00	28	3.08	<b>Clamps</b>	173
								<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** AQP elastomer tube, reinforcement consisting of a helical wire between two textile braids and blue AQP elastomer cover.

**Application:** Suction and transfer applications for petroleum and phosphate ester hydraulic fluids, fuel, lubricating oils, gasoline, water and many other industrial fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

†Maximum working pressure for band clamp type fittings is 50 psi. ‡Sold as bulk hose only.

**FC619**

**Flexible, wire inserted suction**  
**Exceeds SAE100R4**



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
FC619-12	.75	1.21	300†	1200	2.50	25	.46	<b>Global</b>	
FC619-16	1.00	1.48	250†	1000	3.00	25	.56	Skive Nipples	74
FC619-20	1.25	1.75	200†	800	4.00	25	.78	OTC	74
FC619-24	1.50	2.04	150†	600	5.00	25	1.00	TTC	74
FC619-32	2.00	2.55	100†	400	6.00	25	1.23	<b>Sockets</b>	72
								<b>Clamps</b>	173
								<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** Synthetic rubber tube, reinforcement consisting of a helical wire between two textile reinforcement layers and synthetic rubber cover.

**Application:** Suction and transfer applications for petroleum hydraulic fluids, fuel, lubricating oils, gasoline, water and many other industrial fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +275°F (-40°C to +135°C).

**For complete Agency Listings:** See pages 397-398.

†Maximum working pressure for band clamp type fittings is 50 psi.

# FC318

Wire inserted suction  
SAE 100R4



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC318-12	.75	1.25	300†	1200	5.00	28	.42	-40 Crimp	143
FC318-16	1.00	1.50	250†	1000	6.00	28	.50	<b>Global</b>	
FC318-20	1.25	1.80	200†	800	8.00	28	.90	Skive Nipples	74
FC318-24	1.50	2.08	150†	600	10.00	28	1.13	OTC	74
FC318-32	2.00	2.57	100†	400	12.00	28	1.30	TTC	74
FC318-40	2.50	3.07	62	250	14.00	28	1.72	TTC12 (-12 only)	74
FC318-48‡	3.00	3.64	56	225	18.00	28	1.96	<b>Sockets</b>	72
FC318-64‡	4.00	4.69	50	200	24.00	28	3.08	<b>Clamps</b>	173

**Construction:** Synthetic rubber tube, reinforcement consisting of a helical wire between two textile braids and synthetic rubber cover.

**Application:** Suction and transfer applications for petroleum hydraulic fluids, fuel, lubricating oils, gasoline and water. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

†Maximum working pressure for band clamp type fittings is 50 psi. ‡Sold as bulk hose only.

**CRIMP FITTINGS**

-40 Crimp 143

**Global**

Skive Nipples 74

OTC 74

TTC 74

TTC12 (-12 only) 74

**Sockets** 72

**Clamps** 173

**Accessories and Assembly Instructions see page 346.**

# FC466

Textile braid  
Exceeds SAE 100R6 performance\*



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC466-04	.25	.48	400	1600	2.50	28	.06	<b>Global</b>	
FC466-06	.38	.62	400	1600	3.00	28	.10	**Skive Nipples	74
FC466-08	.50	.75	400	1600	4.00	28	.13	OTC	74
FC466-10	.63	.91	350	1400	5.00	18	.18	<b>Sockets</b>	72
FC466-12	.75	1.03	350	1400	7.00	18	.19	<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** Synthetic rubber tube, textile braid reinforcement and polyester braid cover.

**Application:** For gasoline, fuel, lubricating oils, air and water. Not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C), Air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

\*All sizes except -12  
\*\*No skiving required.

**FC498**  
Textile braid  
Exceeds SAE 100R6



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC498-04	.25	.50	400	1600	2.50	28	.08	<i>Global</i>	
FC498-06	.38	.62	400	1600	3.00	28	.13	**Skive Nipples 74	
FC498-08	.50	.78	400	1600	4.00	28	.15	OTC 74	
FC498-10	.63	.91	350	1400	5.00	18	.20	<b>Sockets</b> 72	
FC498-12	.75	1.03	350	1400	7.00	18	.28	<i>Accessories and Assembly Instructions see page 346.</i>	

**Construction:** AQP elastomer tube, textile braid reinforcement, AQP elastomer cover.

**Application:** Low pressure return lines in hydraulic systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

\*\*No skiving required.

**2580**  
Double textile braid



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>REUSABLE FITTINGS</b> 145	
2580-4	.19	.52	1000	4000	3.00		.12	<b>Sockets</b> 73	
2580-5	.25	.58	800	3200	3.38		.15	<i>Accessories and Assembly Instructions see page 346.</i>	
2580-6	.31	.68	650	2600	4.00		.17		
2580-8	.41	.77	625	2500	4.62		.19		
2580-10	.50	.92	600	2400	5.50		.28		
2580-12	.63	1.08	550	2200	6.50		.34		
2580-16	.88	1.24	500	2000	7.38		.36		
2580-20	1.12	1.50	450	1800	9.00		.43		
2580-24	1.38	1.75	400	1600	10.50		.51		
2580-32	1.81	2.22	350	1400	13.25		.75		

**Construction:** Synthetic rubber tube, double textile braid reinforcement and synthetic rubber cover. For larger dash sizes, see Catalog JD1.

**Application:** For water, gasoline, and fuel oil. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

## 2583

Double textile braid  
SAE 100R3

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
2583-4	.25	.57	1250	5000	3.00		.12
2583-6	.38	.75	1125	4500	4.00		.22
2583-8	.50	.94	1000	4000	5.00		.26
2583-12	.75	1.25	750	3000	6.00		.48
2583-16	1.00	1.50	565	2250	8.00		.51
2583-20	1.25	1.75	375	1500	10.00		.73

**Construction:** Synthetic rubber tube, double textile braid reinforcement and synthetic rubber cover.

**Application:** For hydraulics, fuel, lubricating oils, gasoline, air and water. Not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C). Air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

FITTING REFERENCE	PAGE
CRIMP FITTINGS	
Global	
OTC	74
Accessories and Assembly Instructions see page 346.	

## CRIMP FITTINGS

Global

OTC

74

Accessories and Assembly  
Instructions see page 346.

## FC194

## AQP®/HI-IMPULSE®, single wire braid

## Exceeds SAE 100R1A, meets or exceeds DIN 20 022 Type 1ST



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
FC194-04	.25	.63	3250	13000	4.00		.19
FC194-06	.38	.78	3000	12000	5.00		.30
FC194-08	.50	.90	2500	10000	7.00		.39
FC194-10	.63	1.03	2000	8000	8.00		.46
FC194-12	.75	1.19	1800	7200	9.50		.53
FC194-16	1.00	1.50	1300	5200	12.00		.80
FC194-20	1.25	1.81	900	3600	16.50		.98

**Construction:** AQP elastomer tube, single wire braid reinforcement and blue AQP elastomer cover.

**Application:** Hydraulic fluids, petroleum and fire resistant types, fuel, lubricating oils, gasoline, water, and other industrial fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

FITTING REFERENCE	PAGE
CRIMP FITTINGS	
Global	
Skive Nipples	74
Sockets	72
Accessories and Assembly Instructions see page 346.	

## CRIMP FITTINGS

Global

Skive Nipples

74

Sockets

72

Accessories and Assembly  
Instructions see page 346.



**GH194 MATCHMATE BLUE**

AQP®/HI-IMPULSE®, single wire braid

Exceeds SAE 100R1AT, meets or exceeds DIN 20 022 Type 1SN



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								CRIMP FITTINGS	
								Global	
GH194-4	.25	.53	3250	13000	4.00		.17	Skive Nipples	74
GH194-6	.38	.69	3000	12000	5.00		.25	TTC	74
GH194-8	.50	.81	2500	10000	7.00		.30	Sockets	72
GH194-10	.63	.94	2000	8000	8.00		.36	Accessories and Assembly Instructions see page 346.	
GH194-12	.75	1.09	1800	7200	9.50		.46		
GH194-16	1.00	1.41	1300	5200	12.00		.66		
GH194-20	1.25	1.73	900	3600	16.50		.85		

**Construction:** AQP elastomer tube, single wire braid reinforcement and blue AQP elastomer cover.

**Application:** Hydraulic fluids, petroleum and fire resistant types, fuel and lubricating oils, gasoline, water and other industrial fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

**2681**

HI-IMPULSE® single wire braid

Exceeds SAE 100R1A, meets or exceeds DIN 20 022 Type 1ST



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								CRIMP FITTINGS	
								Global	
2681-3	.19	.50	4000	16000	3.50		.13	Skive Nipples	74
2681-4	.25	.62	3250	13000	4.00		.19	Sockets	72
2681-5	.31	.69	3250	13000	4.50		.27	Accessories and Assembly Instructions see page 346.	
2681-6	.38	.78	3000	12000	5.00		.30		
2681-8	.50	.91	2500	10000	7.00		.39		
2681-10	.63	1.03	2000	8000	8.00		.46		
2681-12	.75	1.19	1800	7200	9.50		.53		
2681-16	1.00	1.50	1300	5200	12.00		.80		
2681-20	1.25	1.81	900	3600	16.50		.98		
2681-24	1.50	2.06	700	2800	20.00		1.12		
2681-32	2.00	2.58	600	2400	25.00		1.63		

**Construction:** Synthetic rubber tube, single wire braid reinforcement and synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

**GH663 MATCHMATE Plus HI-IMPULSE®**

Single wire braid meets DIN 20 022 Type 1SN

Exceeds SAE 100R1AT performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
GH663-4	.25	.53	3250 *2750	13000 **11000	4.00		.16	<b>CRIMP FITTINGS</b>	
GH663-6	.38	.69	3000 *2250	12000 9000	5.00		.25	<i>Global</i>	
GH663-8	.50	.81	2500 *2000	10000 **8000	7.00		.30	Skive Nipples	74
GH663-12	.75	1.09	1800 *1250	7200 **5000	9.50		.45	TTC	74
GH663-16	1.00	1.41	1300 *1000	5200 **4000	12.00		.68	<b>Sockets</b>	72
GH663-20	1.25	1.71	950	3770	16.50		.88	<b>REUSABLE FITTINGS</b>	153
GH663-24	1.50	1.99	725	2900	20.00		1.05	<i>Sockets</i>	73
GH663-32	2.00	2.52	580	2320	25.00		1.31	<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** Synthetic rubber tube, single wire braid reinforcement and synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

\*Pressure rating with reusable style fittings. \*\*Burst (min) with reusable style fittings.

**FC211**

Single wire braid

SAE 100R1AT



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
FC211-04	.25	.53	2750	11000	4.00		.15	<b>CRIMP FITTINGS</b>	
FC211-06	.38	.69	2250	9000	5.00		.24	<i>Global</i>	
FC211-08	.50	.81	2000	8000	7.00		.29	Skive Nipples	74
FC211-12	.75	1.09	1250	5000	9.50		.46	TTC	74
FC211-16	1.00	1.41	1000	4000	12.00		.80	<b>Sockets</b>	72
								<b>REUSABLE FITTINGS</b>	153
								<i>Sockets</i>	73

**Construction:** Synthetic rubber tube, single wire braid reinforcement and synthetic rubber cover. This hose has the maximum operating pressure printed in the layline of the hose complying to Virginia Law #1415.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

**Accessories and Assembly Instructions see page 346.**

**GH681**

Single wire braid

Exceeds DIN 20 022 Type 1 performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
GH681-4	.25	.47	3000	12000	2.00		.11	<i>Global</i>	
GH681-6	.38	.63	3000	12000	2.50		.18	Skive Nipples 74	
GH681-8	.50	.78	3000	12000	3.50		.26	TTC (-6 only) 74	
								<b>Sockets</b> 72	

**Construction:** Synthetic rubber tube, single wire braid reinforcement and synthetic rubber cover. Meets or exceeds DIN requirements at 1/2 SAE Bend Radius.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

**Accessories and Assembly Instructions see page 346.**

**GH683**

Single wire braid

Exceeds SAE 100R1



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
GH683-4	.25	.51	3000	12000	2.00		.11	<i>Global</i>	
GH683-6	.38	.67	3000	12000	2.50		.18	**Skive Nipples (-4 & -6 only) 74	
GH683-8	.50	.81	3000	12000	3.50		.26	TTC 74	
								<b>Sockets</b> 72	

**Construction:** Synthetic rubber tube, single wire braid reinforcement and polyester braid cover. 1/2 SAE Bend Radius.

**Application:** For hydraulic, air, gasoline, fuel and lubricating oils. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -50°F to +212°F (-46°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

\*\*No skiving required.

**Accessories and Assembly Instructions see page 346.**

**FC510**  
**AQP®/HI-PAC® wire braid**  
**Exceeds SAE 100R2 performance**



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
FC510-04	.25	.57	5000	20000	3.00		.23	Skive Nipples	74
FC510-06	.38	.69	4000	16000	3.50		.29	TTC	74
FC510-08	.50	.80	3500	14000	5.00		.34	<b>Sockets</b>	72
FC510-10	.63	.93	2750	11000	6.00		.44	<b>REUSABLE FITTINGS</b>	155
FC510-12	.75	1.09	2250	9000	7.00		.52	<b>Sockets</b>	73
FC510-16	1.00	1.37	2000	8000	9.00		.71	<i>Accessories and Assembly Instructions see page 346.</i>	
FC510-20	1.25	1.70	1625	6500	11.00		1.08		

**Construction:** AQP elastomer tube, Hi-Pac braided wire reinforcement and blue AQP elastomer cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

**FC310**  
**HI-PAC® wire braid**  
**SAE 100R16 performance**



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
FC310-04	.25	.55	5000	20000	2.00† 3.00		.21	Skive Nipples	74
FC310-06	.38	.68	4000	16000	2.50† 3.50		.27	TTC	74
FC310-08	.50	.79	3500	14000	3.50† 5.00		.34	<b>Sockets</b>	72
FC310-10	.63	.93	2750	11000	4.00† 6.00		.44	<b>REUSABLE FITTINGS</b>	155
FC310-12	.75	1.08	2250	9000	4.75† 7.00		.50	<b>Sockets</b>	73
FC310-16	1.00	1.36	2000	8000	6.00† 9.00		.71	<i>Accessories and Assembly Instructions see page 346.</i>	
FC310-20	1.25	1.69	1625	6500	8.25† 11.00		1.06		

**Construction:** Synthetic rubber tube, Hi-Pac braided wire reinforcement, synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more specific information on fluid applications, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

†Improved minimum bend radius when used with global fittings.

# FC195

AQP®/HI-IMPULSE® double wire braid

Exceeds SAE 100R2A, meets or exceeds DIN 20 022 Type 2ST



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
FC195-04	.25	.69	5750† 5000	23000† 20000	4.00		.31	Skive Nipples	74
FC195-06	.38	.84	5000† 4000	20000† 16000	5.00		.42	Sockets	72
FC195-08	.50	.97	4250† 3500	17000† 14000	7.00		.51	<b>REUSABLE FITTINGS</b>	
FC195-10	.63	1.09	3250† 2750	14500† 11000	8.00		.59	Sockets	73
FC195-12	.75	1.25	3125† 3000	12500† 9000	9.50		.75	<i>Accessories and Assembly Instructions see page 346.</i>	
FC195-16	1.00	1.56	2500† 2000	10000† 8000	12.00		1.04		
FC195-20	1.25	2.00	2250† 1625	9000† 6500	16.50		1.68		
FC195-24	1.50	2.25	1800† 1750	7200† 5000	20.00		1.91		
FC195-32	2.00	2.75	1500† 1250	6000† 4500	25.00		2.39		

**Construction:** AQP elastomer tube, double wire braid reinforcement and blue AQP elastomer cover.  
**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).  
**For complete Agency Listings:** See pages 397-398.  
 †Improved pressure performance when used with global fittings.

# GH195 MATCHMATE BLUE

AQP®/HI-IMPULSE® double wire braid

Exceeds SAE 100R2AT, meets or exceeds DIN 20 022 Type 2SN



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
GH195-4	.25	0.60	5750	23000	4.00		0.27	Skive Nipples	74
GH195-6	.38	0.75	5000	20000	5.00		0.39	TTC	74
GH195-8	.50	0.87	4250	17000	7.00		0.46	Sockets	72
GH195-10	.63	0.99	3250	13000	8.00		0.54	<i>Accessories and Assembly Instructions see page 346.</i>	
GH195-12	.75	1.16	3000	12000	9.50		0.67		
GH195-16	1.00	1.49	2500	10000	12.00		0.97		
GH195-20	1.25	1.92	2250	9000	16.50		1.60		
GH195-24	1.50	2.15	1750	7000	20.00		1.74		
GH195-32	2.00	2.67	1500	6000	25.00		2.27		

**Construction:** AQP elastomer tube, double wire braid reinforcement and blue AQP elastomer cover.  
**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).  
**For complete Agency Listings:** See pages 397-398.

HOSE

HYDRAULIC

## 2781

**HI-IMPULSE®** double wire braid

Exceeds SAE 100R2A, meets or exceeds DIN 20 022 Type 2ST



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
2781-4*	.25	.69	5750† 5000	23000† 20000	4.00		.33	<i>Global</i>	
2781-6	.38	.84	5000† 4000	20000† 16000	5.00		.45	Skive Nipples	74
2781-8	.50	.97	4250† 3500	17000† 14000	7.00		.56	<b>Sockets</b>	72
2781-10	.63	1.09	3625† 3250	14500† 11000	8.00		.62	<b>REUSABLE FITTINGS</b>	158
2781-12	.75	1.25	3125† 3000	12500† 9000	9.50		.80	<b>Sockets</b>	73
2781-16	1.00	1.56	2500† 2000	10000† 8000	12.00		1.06	<i>Accessories and Assembly</i>	
2781-20	1.25	2.00	2250† 1625	9000† 6500	16.50		1.73	<i>Instructions see page 346.</i>	
2781-24	1.50	2.25	1800† 1750	7200† 5000	20.00		2.05		
2781-32	2.00	2.75	1500† 1250	6000† 4500	25.00		2.70		

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover.**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).**For complete Agency Listings:** See pages 397-398.

†Improved pressure performance when used with global fittings.

\*Approved for 10,000 psi maximum operating pressure for static Jack Hose applications.

**GH781 MATCHMATE Plus™ / HI-IMPULSE®**

Double wire braid exceeds DIN 20 022 Type 2 performance

Exceeds SAE 100R16



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
GH781-4*	.25	.53	5800	23200	2.00		.22	<i>Global</i>	
GH781-6	.38	.69	5000	20000	2.50		.29	Skive Nipples	74
GH781-8	.50	.81	4250	17000	3.50		.39	TTC	74
GH781-10	.63	.93	3625	14500	4.00		.44	<b>Sockets</b>	72
GH781-12	.75	1.10	3125	12500	4.75		.53	<i>Accessories and Assembly</i>	
GH781-16	1.00	1.42	2500	10000	6.00		.72	<i>Instructions see page 346.</i>	
GH781-20	1.25	1.65	2250	9000	8.25		1.09		
GH781-24	1.50	2.03	1800	7200	10.00		1.40		
GH781-32	2.00	2.53	1300	5200	12.50		1.90		

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover. Meets or exceeds DIN requirements at 1/2 SAE Bend Radius.**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).**For complete Agency Listings:** See pages 397-398.

\*Approved for 10,000 psi maximum operating pressure for static Jack Hose applications.

**GH793 MATCHMATE Plus HI-IMPULSE®**

Double wire braid meets or exceeds DIN 20 022 Type 2SN,  
Exceeds SAE 100R2AT performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
	#							<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
GH793-4	.25	.60	5750 *5000	23000 *20000	4.00		.26	Skive Nipples	74
GH793-6	.38	.75	5000 *4000	20000 *16000	5.00		.38	TTC	74
GH793-8	.50	.87	4250 *3500	17000 *14000	7.00		.46	<b>Sockets</b>	72
GH793-10	.63	.98	3625 *2750	14500 *11000	8.00		.54	<b>REUSABLE FITTINGS</b>	163
GH793-12	.75	1.16	3125 *2250	12500 *9000	9.50		.66	<b>Sockets</b>	73
GH793-16	1.00	1.50	2500 *2000	10000 *8000	12.00		1.01	<i>Accessories and Assembly Instructions see page 346.</i>	
GH793-20	1.25	1.92	2250	9000	16.50		1.54		
GH793-24	1.50	2.15	1800	7200	20.00		1.68		
GH793-32	2.00	2.51	1300	5200	25.00		2.22		

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

\*Pressure rating with reusable fittings.

**FC212**

Double wire braid  
SAE 100R2AT



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
	#							<b>CRIMP FITTINGS</b>	
								<i>Global</i>	
FC212-04	.25	.60	5000	20000	4.00		.27	Skive Nipples	74
FC212-06	.38	.75	4000	16000	5.00		.38	TTC	74
FC212-08	.50	.88	3500	14000	7.00		.46	<b>Sockets</b>	72
FC212-12	.75	1.16	2250	9000	9.50		.66	<b>REUSABLE FITTINGS</b>	163
FC212-16	1.00	1.50	2000	8000	12.00		1.00	<b>Sockets</b>	73
FC212-20	1.25	1.89	1625	6500	16.50		1.51	<i>Accessories and Assembly Instructions see page 346.</i>	
FC212-24	1.50	2.15	1250	5000	20.00		1.75		
FC212-32	2.00	2.51	1125	4500	25.00		2.25		

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover. This hose has the maximum operating pressure printed in the layline of the hose complying to Virginia Law #1415.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

# 1529

Double wire braid  
High pressure air SAE 100R2A



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
1529-4	.25	.69	5000	20000	4.00		.34	<i>Global</i>	
1529-6	.38	.84	4000	16000	5.00		.44	Skive Nipples	74
1529-8	.50	.97	3500	14000	7.00		.64	<b>Sockets</b>	72
1529-10	.63	1.09	2750	11000	8.00		.65	<b>REUSABLE FITTINGS</b>	158
1529-12	.75	1.25	2250	9000	9.50		.82	<b>Sockets</b>	73
1529-16	1.00	1.56	2000	8000	12.00		1.00	<i>Accessories and Assembly Instructions see page 346.</i>	
1529-20	1.25	2.00	1625	6500	16.50		1.95		
1529-24	1.50	2.25	1250	5000	20.00		2.02		
1529-32	2.00	2.75	1125	4500	25.00		2.70		

**Construction:** Synthetic rubber tube, double wire braid reinforcement, textile braid and perforated synthetic rubber cover to prevent blistering when used for pneumatic applications.

**Application:** High pressure pneumatic and gaseous applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404. NOTE: Extreme caution is warranted in the use of any hose in any high pressure pneumatic or gaseous application.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

# 2766

Double wire braid  
MIL-DTL-13531, Type II, Class A



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
2766-4	.25	.69	5000	20000	4.00		.32	<i>Global</i>	
2766-6	.38	.84	4000	16000	5.00		.46	Skive Nipples	74
2766-8	.50	.97	3500	14000	7.00		.54	<b>Sockets</b>	72
2766-12	.75	1.25	2250	9000	9.50		.75	<b>REUSABLE FITTINGS</b>	158
2766-16	1.00	1.56	2000	8000	11.00		1.02	<b>Sockets</b>	73
2766-20	1.25	2.00	1625	6500	16.00		1.63	<i>Accessories and Assembly Instructions see page 346.</i>	
2766-24	1.50	2.25	1250	5000	20.00		1.94		
2766-32	2.00	2.75	1000	4500	22.00		2.69		

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover.

**Application:** High pressure hydraulics, fuel and lubricating oil and gasoline. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F (-54°C to +93°C).

**For complete Agency Listings:** See pages 397-398.



**GH120 MATCHMATE ICE™**

Cold temperature applications  
SAE 100R16 performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE PAGE	
								INCHES	INCHES
								<b>CRIMP FITTINGS</b>	
GH120-4	0.25	0.56	5000	20000	2.00		.20	<b>Global</b>	
GH120-6	0.38	0.68	4000	16000	2.50		.27	Skive Nipples (-4 through -20)	74
GH120-8	0.50	0.82	3500	14000	3.50		.39	TTC	74
GH120-10	0.63	0.98	2750	11000	4.00		.50	<b>Sockets</b>	72
GH120-12	0.75	1.12	2250	9000	4.75		.62	<b>Accessories and Assembly Instructions see page 346.</b>	
GH120-16	1.00	1.41	2000	8000	6.00		.82		
GH120-20	1.25	1.71	1625	6500	8.25		1.07		
GH120-24	1.50	2.03	1250	5000	10.00		1.42		
GH120-32	2.00	2.51	1125	4500	12.50		1.88		

**Construction:** Aeroquip exclusive low temperature compound tube and cover, double wire braid reinforcement.

**Application:** Low temperature flexing and hydraulic system service with petroleum and water-base fluids. For use in frigid environments on construction equipment and other mobile applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -70°F to +212°F (-57°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

**FC639**

Constant pressure hose  
SAE 100R17



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE PAGE	
								INCHES	INCHES
								<b>CRIMP FITTINGS</b>	
FC639-04	0.25	.52	3000	12000	2.00		.15	<b>Global</b>	
FC639-06	0.38	.67	3000	12000	2.50		.23	Skive Nipples	74
FC639-08	0.50	.81	3000	12000	3.50		.32	TTC (-4 through -12)	74
FC639-10**	0.63	1.00	3000	12000	4.00		.51	<b>Sockets</b>	72
FC639-12**	0.75	1.14	3000	12000	4.75		.63	<b>Accessories and Assembly Instructions see page 346.</b>	
FC639-16**	1.00	1.43	3000	12000	6.00		.83		

**Construction:** Synthetic rubber tube with one or two wire braid reinforcements, fire and ozone resistant synthetic rubber cover.

**Application:** General industrial and hydraulic system service with petroleum and water-base fluids. Recommended for high-pressure oil lines used on construction equipment and other off-highway applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

\*\*Two braids of high tensile wire.

## FC735 BRUISER™

Double wire braid

Exceeds DIN 20 022 Type 2SN *HI-IMPULSE*® at 1/2 SAE bend radius



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
FC735-04*	.25	.53	5000*	20000*	2.00		.22	<i>Global</i>	
FC735-06	.38	.69	5000	20000	2.50		.29	Skive Nipples	74
FC735-08	.50	.81	4250	17000	3.50		.39	TTC	74
FC735-10	.63	.93	3625	14500	4.00		.44	<b>Sockets</b>	72
FC735-12	.75	1.10	3125	12500	4.75		.53	<i>Accessories and Assembly Instructions see page 346.</i>	
FC735-16	1.00	1.42	2500	10000	6.00		.72		
FC735-20	1.25	1.70	2250	9000	8.25		1.09		

**Construction:** Synthetic rubber tube, double wire braid reinforcement, synthetic rubber intermediate cover, and BRUISER outer cover. Meets or exceeds DIN requirements at 1/2 SAE bend radius.

**Application:** High abrasion applications. Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C). Maximum ambient temperature: 180°F (82°C).

**For complete Agency Listings:** See pages 397-398.

\*Meets SAE100R2 pressures.

## FC736 BRUISER™

Four heavy spiral wire

Exceeds SAE 100R12



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
FC736-06	.38	.79	5500*	22000*	5.00		.47	Spiral Single Skive Crimp	108
FC736-08	.50	.92	5000*	20000*	7.00		.59	Internal Skive Crimp (-16 & -20 only)	123
FC736-10	.63	1.11	5000*	20000*	9.50		.80	<i>Global</i>	
FC736-12	.75	1.20	4000	16000	9.50		.92	TTC12	74
FC736-16	1.00	1.48	4000	16000	12.00		1.22	<b>Sockets</b>	72
FC736-20	1.25	1.83	3000	12000	16.50		1.64	<b>REUSABLE FITTINGS</b>	165

**Construction:** Synthetic rubber tube, 4-heavy spiral wire reinforcement, synthetic rubber intermediate cover, and BRUISER outer cover.

**Application:** High abrasion applications. Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C). Maximum ambient temperature: 180°F (82°C).

**For complete Agency Listings:** See pages 397-398.

\*4,000 psi working pressure and 16,000 psi burst with TTC12 fittings.

**Sockets** 73  
*Accessories and Assembly Instructions see page 346.*

GH493 **MATCHMATE Plus™**

Four heavy spiral wire

SAE 100R12



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE PAGE	
								<b>CRIMP FITTINGS</b>	
GH493-6**	.38	.79	4000	16000	5.00		.47	Spiral Single Skive Crimp	108
GH493-8	.50	.92	4000	16000	7.00		.59	<b>Global</b> TTC12	74
GH493-10	.63	1.11	4000	16000	9.50		.69	<b>Sockets</b>	72
GH493-12	.75	1.20	4000	16000	9.50		.92	<b>REUSABLE FITTINGS</b>	165
GH493-16	1.00	1.48	4000	16000	12.00		1.22	<b>Sockets</b>	73
GH493-20	1.25	1.83	3000	12000	16.50		1.64	<b>Accessories and Assembly Instructions see page 346.</b>	
GH493-24	1.50	2.12	2500	10000	20.00		2.10		
GH493-32	2.00	2.64	2500	10000	25.00		2.81		

**Construction:** Synthetic rubber tube, 4 spiral wire reinforcement, black synthetic rubber cover.

**Application:** Hydraulic systems service with petroleum and water-base fluids, for general industrial use. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

*\*\*Approved for 10,000 psi maximum operating pressure for static Jack Hose applications.*

## FC136

Four heavy spiral wire

Exceeds SAE 100R12



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE PAGE	
								<b>CRIMP FITTINGS</b>	
FC136-06**	.38	.79	5500 4000*	22000 16000*	5.00		.45	Spiral Single Skive Crimp	108
FC136-08	.50	.92	5000 4000*	20000 16000*	7.00		.60	Internal Skive Crimp (-16 through -32)	123
FC136-10	.63	1.11	5000 4000*	20000 16000*	9.50		.67	<b>Global</b> TTC12	74
FC136-12	.75	1.20	4000	16000	9.50		.90	<b>Sockets</b>	72
FC136-16	1.00	1.48	4000	16000	12.00		1.19	<b>REUSABLE FITTINGS</b>	165
FC136-20	1.25	1.83	3000	12000	16.50		1.60	<b>Sockets</b>	73
FC136-24	1.50	2.12	2500	10000	20.00		2.01	<b>Accessories and Assembly Instructions see page 346.</b>	
FC136-32	2.00	2.64	2500	10000	25.00		2.93		

**Construction:** Synthetic rubber tube, 4-heavy spiral wire reinforcement, synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial use. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

*\*Pressure rating with TTC12 fittings.*

*\*\*Approved for 10,000 psi maximum operating pressure for static Jack Hose applications.*

# FC659

Four spiral wire  
Exceeds SAE 100R12



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
FC659-06	.38	.79	4000	16000	2.50*		.47
FC659-08	.50	.92	4000	16000	3.50*		.57
FC659-10	.63	1.11	4000	16000	4.75*		.70
FC659-12	.75	1.20	4000	16000	4.75*		.90
FC659-16	1.00	1.48	4000	16000	6.00*		1.21
FC659-20	1.25	1.83	3000	12000	8.25*		2.40

FITTING REFERENCE	PAGE
<b>CRIMP FITTINGS</b>	
<i>Global</i>	
TTC12	74
<i>Accessories and Assembly Instructions see page 346.</i>	

**Construction:** Synthetic rubber tube, 4 spiral wire reinforcement and synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids requiring premium performance and flexibility. For more specific information on fluid applications, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

\*1/2 SAE bend radius.

# FC254

Four heavy spiral wire  
Exceeds SAE 100R11 performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
FC254-08*	.50	.98	7500†	30000	8.00		.69
FC254-12	.75	1.26	6250	25000	11.00		1.12
FC254-16	1.00	1.52	5000	20000	12.00		1.31
FC254-20	1.25	1.80	4000	16000	16.50		2.05
FC254-24	1.50	2.13	3000	12000	20.00		2.35
FC254-32	2.00	2.68	3000	12000	25.00		3.13

FITTING REFERENCE	PAGE
<b>CRIMP FITTINGS</b>	
Spiral Single Skive Crimp (-20, -24 only)	116, 108
Internal Skive Crimp	123
<i>Global</i>	
Spiral TTC™	100
<b>Sockets</b>	72
<i>Accessories and Assembly Instructions see page 346.</i>	

**Construction:** Synthetic rubber tube, 4-heavy spiral wire reinforcement and synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial use. For more specific information on fluid applications, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

†Rated at 10,000 psi for water blast applications using internal skive fittings.

\*Available with Bruiser cover as FC854-08.

# FC273

Four or six spiral wire  
SAE 100R13



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC273-12	.75	1.26	5000	20000	9.50		1.08	Spiral Single Skive Crimp	116
FC273-16	1.00	1.52	5000	20000	12.00		1.41	Internal Skive Crimp	128
FC273-20	1.25	1.96	5000	20000	16.50		2.53	<b>Global</b> Spiral TTC™	100
FC273-24	1.50	2.26	5000	20000	20.00		3.35	<b>Sockets</b>	72
FC273-32	2.00	2.80	5000	20000	25.00		5.00	<i>Accessories and Assembly Instructions see page 346.</i>	

**Construction:** Synthetic rubber tube, multiple heavy spiral wire (4 wire for -12, -16; 6 wire for -20, -24 and -32); black synthetic rubber cover.

**Application:** Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

# FC323

Four spiral wire

Exceeds performance requirements SAE 100R12 (-20), SAE 100R11 (-24, -32)



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC323-12	.75	1.20	3000	12000	9.50		.94	Spiral Single Skive Crimp (-12 through -24)	108
FC323-16	1.00	1.48	3000	12000	12.00		1.22	Internal Skive Crimp	123
FC323-20	1.25	1.86	3000	12000	16.50		1.70	<b>Sockets</b>	72
FC323-24	1.50	2.11	3000	12000	20.00		2.20	<i>Accessories and Assembly Instructions see page 346.</i>	
FC323-32	2.00	2.63	3000	12000	25.00		3.21		

**Construction:** AQP elastomer tube, 4-spiral wire reinforcement and a blue AQP elastomer cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

HOSE

HYDRAULIC

# FC324

Four spiral wire  
Exceeds SAE 100R12



HOSE

Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
								<b>CRIMP FITTINGS</b>	
FC324-08	.50	.91	4000	16000	7.00		.61	Spiral Single Skive Crimp (-12 & -16 only)	108, 115
FC324-12	.75	1.20	4000	16000	9.50		.99	Internal Skive Crimp (-12, -16)	123
FC324-16	1.00	1.48	4000	16000	12.00		1.29	<b>Sockets</b>	72

**Construction:** AQP elastomer tube, 4-spiral wire reinforcement and a blue AQP elastomer cover.  
**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).  
**For complete Agency Listings:** See pages 397-398.

<b>REUSABLE FITTINGS</b> (-8 only)	165
<b>Sockets</b>	73
<i>Accessories and Assembly Instructions see page 346.</i>	

# FC325

Four spiral wire  
Exceeds SAE 100R13



HYDRAULIC

Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
								<b>CRIMP FITTINGS</b>	
FC325-12	.75	1.26	5000	20000	9.50		1.09	Internal Skive Crimp	130
FC325-16	1.00	1.52	5000	20000	12.00		1.42	<b>Sockets</b>	72

**Construction:** AQP elastomer tube, 4-spiral wire reinforcement and a blue AQP elastomer cover.  
**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).  
**For complete Agency Listings:** See pages 397-398.

<i>Accessories and Assembly Instructions see page 346.</i>	
--	--

**FC606**  
Six spiral wire  
SAE 100R15



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC606-16	1.00	1.65	6000	24000	12.00		1.79	Internal Skive Crimp	134
FC606-20	1.25	1.95	6000	24000	16.50		2.43	<i>Global</i> Spiral TTC™	100
FC606-24*	1.50	2.30	6000	24000	20.00		3.17	<i>Sockets</i>	72

**Construction:** Synthetic rubber tube, 6-spiral wire reinforcement, synthetic rubber cover.

**Application:** High pressure hydraulics, hydrostatic transmissions. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C). FC606-24 -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

\*Factory made assemblies only. Contact Eaton Aeroquip.

*Accessories and Assembly Instructions see page 346.*

**GH506**  
Four spiral wire  
DIN 20023 T2, EN 856 Type 4SH



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
GH506-12	.75	1.27	6090	24360	11.00		1.43	Global Spiral TTC™	100
GH506-16	1.00	1.51	5510	22040	13.38		4.96	<i>Accessories and Assembly Instructions see page 346.</i>	
GH506-20	1.25	1.79	5075	20300	18.11		5.51		

**Construction:** Synthetic rubber tube, 4 spiral wire reinforcement, synthetic rubber cover.

**Application:** Four wire hose for high pressure hydraulic systems with petroleum and water-base fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

## GH466

### Six spiral wire



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								CRIMP FITTINGS Global Spiral TTC™ <i>Accessories and Assembly Instructions see page 346.</i>	100
GH466-20	1.25	1.94	5510	22040	16.50		7.67		

**Construction:** Synthetic rubber tube, 6 spiral wire reinforcement, synthetic rubber cover.

**Application:** Six wire spiral hose for pressure systems with extreme pressure peaks. For use with petroleum and water-base fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

## FC611

### Single wire braid medium pressure EPDM hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								CRIMP FITTINGS <i>Global</i> TTC <i>Accessories and Assembly Instructions see page 346.</i>	74
FC611-04	.25	.53	3000	12000	4.00	28	.16		
FC611-06	.38	.68	2250	9000	5.00	28	.22		
FC611-08	.50	.80	2000	8000	7.00	28	.28		
FC611-12	.75	1.10	1250	5000	9.50	28	.43		
FC611-16	1.00	1.41	1000	4000	12.00	20	.60		
FC611-20	1.25	1.71	625	2500	16.50	20	.80		
FC611-24	1.50	1.99	500	2000	20.00	15	1.02		
FC611-32	2.00	2.52	375	1500	25.00	15	1.28		

**Construction:** Synthetic EPDM tube, single wire braid reinforcement and green EPDM synthetic cover.

**Application:** Ground support equipment (GSE), industrial phosphate-ester based fluids, water glycol systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +175°F (-40°C to +75°C).

**For complete Agency Listings:** See pages 397-398.



## FC693

### Double wire braided high pressure EPDM hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								CRIMP FITTINGS	
FC693-04	.25	.60	5000	20000	4.00		.25	Global	
FC693-06	.38	.75	4000	16000	5.00		.36	TTC 74	
FC693-08	.50	.87	3500	14000	7.00		.40	Accessories and Assembly Instructions see page 346.	

**Construction:** Synthetic EPDM tube, double wire braid reinforcement and green EPDM synthetic cover.

**Application:** Ground support equipment (GSE), industrial phosphate-ester based fluids, water glycol systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +175°F (-40°C to +75°C).

**For complete Agency Listings:** See pages 397-398.

## FC636

### Four spiral wire high pressure EPDM hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								CRIMP FITTINGS	
FC636-12	.75	1.20	4000	16000	9.50		.88	Global	
FC636-16	1.00	1.48	4000	16000	12.00		1.17	TTC12 74	
FC636-20	1.25	1.83	3000	12000	16.50		1.55	Accessories and Assembly Instructions see page 346.	
FC636-24	1.50	2.12	2500	10000	20.00		1.96		

**Construction:** Synthetic EPDM tube, 4-spiral wire reinforcement, and green EPDM synthetic cover.

**Application:** Ground support equipment (GSE), industrial phosphate-ester based fluids, water glycol systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +175°F (-40°C to +75°C).

**For complete Agency Listings:** See pages 397-398.



# FC332

Textile braid

Low pressure **SOCKETLESS™**



HOSE

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>REUSABLE FITTINGS</b> Accessories and Assembly Instructions see page 346.	168
FC332-04	.25	.49	250	1000	3.00	28	.08		
FC332-06	.38	.63	250	1000	3.00	28	.12		
FC332-08	.50	.75	250	1000	5.00	28	.15		
FC332-10	.63	.91	250	1000	6.00	18	.20		
FC332-12	.75	1.04	250	1000	7.00	18	.28		

**Construction:** AQP elastomer tube, textile braid reinforcement, AQP elastomer cover.

**Application:** For gasoline, fuel and lubricating oils, air and water. Not recommended for hydraulic impulse applications and is not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C). Air not to exceed +250°F (+121°C) and water not to exceed +180°F (+82°C).

**For complete Agency Listings:** See pages 397-398.

# FC647

Textile braid low pressure **SOCKETLESS™**

Fire resistant meets RMA/CGA flame test requirements



SPECIAL APPLICATION

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>REUSABLE FITTINGS</b> Accessories and Assembly Instructions see page 346.	168
FC647-04*	.25	.52	360	1440	3.00	28	.06		
FC647-06*	.38	.66	300	1200	3.00	28	.09		
FC647-08*	.50	.79	300	1200	5.00	28	.12		
FC647-10*	.63	.92	250	1000	6.00	18	.16		
FC647-12*	.75	1.05	250	1000	7.00	18	.18		

**Construction:** Synthetic rubber tube, textile braid reinforcement, polyester braided cover.

**Application:** For gasoline, fuel and lubricating oils, air and water. Not recommended for hydraulic impulse applications and not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C). Water not to exceed +150°F (+66°C), air not to exceed +165°F (+74°C).

**For complete Agency Listings:** See pages 397-398.

*\*NOTE: You must insert the correct color code in the complete part number. Color codes are BLK = black, BLU = blue, BRN = Brown, GRN = green, WHT = white. Example: FC647-04GRN is a green cover in dash size 4.*



**2556/2565**

Textile braid

Low pressure **SOCKETLESS™**

Meets performance requirements SAE 30R2 Type 1



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	168
								Accessories and Assembly Instructions see page 346.	
2556-4	.25	.49	360	1440	3.00	28	.08		
2556-6	.38	.62	300	1200	3.00	28	.14		
2556-8	.50	.75	300	1200	5.00	28	.17		
2556-10	.63	.91	250	1000	6.00	18	.22		
2556-12	.75	1.03	250	1000	7.00	18	.26		
2565-4	.25	.50	300	1250	2.25	20	.09		
2565-6	.38	.63	250	1000	3.00	20	.12		
2565-8	.50	.78	200	750	3.75	10	.17		
2565-10	.63	.97	175	700	4.75	10	.39		
2565-12	.75	1.09	125	500	5.50	10	.33		

**Construction:** Synthetic rubber tube, textile braid reinforcement, synthetic rubber cover.


**Application:** For gasoline, fuel and lubricating oils, air and water. Not recommended for hydraulic impulse applications and not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404. 2565 is a low temperature synthetic rubber covered MIL-DTL-13444 Type 1, Class A hose.

**Operating Temperature Range:** 2556: -40°F to +212°F (-40°C to +100°C). Water not to exceed +150°F (+66°C), air not to exceed +160°F (+71°C). 2565: -65°F to +250°F (-54°C to +121°C). Water not to exceed +150°F (+66°C), air not to exceed +165°F (+74°C).

For complete Agency Listings: See pages 397-398.

**2575**

Textile braid color coded

Low pressure **SOCKETLESS™**

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	168
								Accessories and Assembly Instructions see page 346.	
2575-4†	.25	.47	250	1000	3.00		.09		
2575-6†	.38	.62	250	1000	4.00		.13		
2575-8†	.50	.75	250	1000	5.00		.17		
2575-10†	.63	.91	200	800	6.00		.20		
2575-12†	.75	1.03	200	800	7.00		.22		

**Construction:** Synthetic rubber tube, textile braid reinforcement, synthetic rubber cover.

**Application:** For gasoline, fuel and lubricating oils, air and water. Not recommended for hydraulic impulse applications and is not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C). Water not to exceed +150°F (+66°C), air not to exceed +160°F (+71°C).

For complete Agency Listings: See pages 397-398.

†NOTE: You must insert the correct color code in the complete part number. Color codes are BLK = black, BLU = blue, GRA = gray, GRN = green, RED = red, YEL = yellow. Example: 2575-4BLU is a blue cover in dash size 4.

## FB9218/FB9219/FB9220

Polyon recoil air hose assemblies



Assembly Part Number	Hose I.D.	Assembly Length	Male NPT NPT Each End, Size	Retracted Length Nominal	Rec. Max. Work Length	Outside Coil Dia.
	INCHES	FEET	INCHES	INCHES	FEET	INCHES
#	○					
FB9218-12	.25	12	1/4-18	6	10	3
FB9218-25	.25	25	1/4-18	12	22	3
FB9218-50	.25	50	1/4-18	23	45	3
FB9219-12	.38	12	3/8-18	5	10	5 1/2
FB9219-25	.38	25	3/8-18	10	21	5 1/2
FB9219-50	.38	50	3/8-18	20	42	5 1/2
FB9220-12	.50	12	1/2-14	5	9	8
FB9220-25	.50	25	1/2-14	9	18	8
FB9220-50	.50	50	1/2-14	18	37	8

*Assemblies provided with fittings attached.*

**Construction:** Red nylon coiled tubing; Male NPT swivel fittings and spring guards at both ends.

**Application:** Air up to 180 psi maximum all sizes.

**Operating Temperature Range:** -40°F to +180°F (-40°C to +82°C).

**Note:** Aeroquip Polyon recoil air hose swivel assemblies are not recommended or approved for air brake application.

**Bulk Hose:** Order part number FC341-04 (1/4"), FC341-06 (3/8"), FC341-08 (1/2").

**For complete Agency Listings:** See pages 397-398.

## SAFETY BLOW GUN 1/4" Female NPT Port



**Maximum outlet pressure:** 30 psi. Conforms to OSHA standards.

**Part Number:** FF9791-01



# FC300

## Single wire braid

### Exceeds SAE 100R5



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								REUSABLE FITTINGS	145
								Sockets	73
								Accessories and Assembly Instructions see page 346.	
FC300-04	.19	.52	3000	12000	3.00	28	.13		
FC300-05	.25	.58	3000	12000	3.38	28	.16		
FC300-06	.31	.67	2250	9000	4.00	28	.23		
FC300-08	.41	.76	2000	8000	4.62	28	.26		
FC300-10	.50	.93	1750	7000	5.50	28	.37		
FC300-12	.63	1.08	1500	6000	6.50	28	.46		
FC300-16	.88	1.27	800	3200	7.38	20†	.44		
FC300-20	1.12	1.50	625	2500	9.00	20†	.52		
FC300-24	1.38	1.75	500	2000	10.50	15†	.67		
FC300-32‡	1.81	2.22	300	1200	13.25	11†	.94		
FC300-40	2.38	2.88	300	1200	24.00	8†	1.50		

**Construction:** AQP elastomer tube, polyester inner braid, single wire braid reinforcement and blue polyester braid cover.  
**Application:** Hydraulics handling petroleum base fluids and air, gasoline, fuel and lubricating oils, fire resistant hydraulic fluids and other industrial fluids. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -55°F to +300°F (-49°C to +150°C). Air not to exceed +250°F (+121°C).  
**For complete Agency Listings:** See pages 397-398.

†Maximum negative pressure shown for -16 and larger are suitable for those which has suffered no external damage or kinking. If greater negative pressures are required for -16 and larger hoses, the use of an internal support coil is recommended.  
 ‡ Does not comply with SAE 100R5 operating pressure of 350 psi or minimum burst of 1400 psi.

# 1503

## Single wire braid

### SAE 100R5



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								REUSABLE FITTINGS	145
								Sockets	73
								Accessories and Assembly Instructions see page 346.	
1503-4	.19	.52	3000	12000	3.00	28	.13		
1503-5	.25	.58	3000	12000	3.38	28	.16		
1503-6	.31	.68	2250	9000	4.00	28	.23		
1503-8	.41	.77	2000	8000	4.62	28	.26		
1503-10	.50	.92	1750	7000	5.50	28	.37		
1503-12	.63	1.08	1500	6000	6.50	28	.46		
1503-16	.88	1.23	800	3200	7.38	20†	.44		
1503-20	1.12	1.50	625	2500	9.00	20†	.52		
1503-24	1.38	1.75	500	2000	10.50	15†	.67		
1503-32	1.81	2.23	350	1400	13.25	11†	.94		
1503-40	2.38	2.88	350	1400	24.00	11†	1.43		

**Construction:** Synthetic rubber tube, textile inner braid, single wire braid reinforcement and synthetic rubber impregnated textile braid cover.  
**Application:** For hydraulics, air, gasoline, fuel and lubricating oils. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C). Air not to exceed +160° F (+71°C).  
**For complete Agency Listings:** See pages 397-398.

†Maximum negative pressures shown for -16 and larger are suitable only for those which has suffered no external damage or kinking. If greater negative pressures are required for -16 and larger hoses, the use of an internal support coil is recommended.

# 303/302A

## Single wire braid

### MIL-H-8794



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	145
303-4	.19	.52	3000	12000	3.00	28	.15	Sockets	73
303-5	.25	.58	3000	10000	3.38	28	.19	Accessories and Assembly Instructions see page 346.	
303-6	.31	.68	2000	9000	4.00	28	.22		
303-8	.41	.77	2000	8000	4.62	28	.26		
303-10	.50	.92	1750	7000	5.50	28	.36		
303-12	.63	1.08	1500	6000	6.50	28	.42		
302A16	.88	1.23	800	3200	7.38	28	.39		
302A20	1.12	1.50	600	2500	9.00	28	.51		
302A24	1.38	1.75	500	2000	11.00	28	.64		
302A32	1.81	2.22	350	1400	13.25	28	1.00		

**Construction:** Synthetic rubber tube, textile inner braid, single wire braid reinforcement and synthetic rubber impregnated textile braid cover.

**Application:** For hydraulics, air, gasoline, fuel and lubricating oils. Air not to exceed +160°F (+71°C). For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** 303 hose: -65°F to +250°F (-54°C to +121°C). 302A hose: -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

# 2651

## Single wire braid

### SAE 100R5 performance



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	145
2651-4	.19	.52	3000	12000	3.00	28	.13	Sockets	73
2651-5	.25	.58	3000	12000	3.38	28	.16	Accessories and Assembly Instructions see page 346.	
2651-6	.31	.68	2250	9000	4.00	28	.23		
2651-8	.41	.75	2000	8000	4.62	28	.26		
2651-10	.50	.92	1750	7000	5.50	28	.37		
2651-12	.63	1.08	1500	6000	6.50	28	.46		
2651-16	.88	1.23	800	3200	7.38	20†	.44		
2651-20	1.12	1.50	625	2500	9.00	20†	.52		
2651-24	1.38	1.75	500	2000	10.50	15†	.67		
2651-32	1.81	2.22	350	1400	13.25	11†	.94		
2651-40	2.38	2.88	350	1400	24.00	11†	1.43		

**Construction:** Synthetic rubber tube, textile inner braid, single wire braid reinforcement, outer textile braid and synthetic rubber cover.

**Application:** Hydraulics, gasoline, fuel and lubricating oils, air and water. Air not to exceed 250 psi or +160°F (+71°C). For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

†Maximum negative pressures shown for -16 and larger are suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required for -16 and larger hoses, the use of an internal support coil is recommended.

This page is part of a complete catalog which contains technical and safety data that must be reviewed when selecting a product.

# FC234

Fuel and oil

Fire resistant USCG/MMT, NMMA/BIA



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								REUSABLE FITTINGS	145
FC234-05	.25	.58	1500	6000	1.00	28	.22	Sockets	73
FC234-06	.31	.68	1500	6000	1.25	28	.25	Accessories and Assembly Instructions see page 346.	
FC234-08	.41	.76	1250	5000	1.75	28	.30		
FC234-10	.50	.94	1250	5000	2.25	28	.45		
FC234-12	.63	1.08	750	3000	2.75	20	.48		
FC234-16	.88	1.24	400	1600	3.50	16	.51		

**Construction:** AQP elastomer tube, brass plated steel wire reinforcement, braided refractory insulation and blue AQP elastomer cover.

**Application:** Diesel fuel, gasoline, hot lube oil and water. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

# FC355

Engine & air brake

FMVSS106



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								REUSABLE FITTINGS	145
FC355-04	.19	.52	1500	6000	.75	28	.17	Sockets	73
FC355-05	.25	.58	1500	6000	1.00	28	.20	Accessories and Assembly Instructions see page 346.	
FC355-06	.31	.68	1500	6000	1.25	28	.24		
FC355-08	.41	.77	1250	5000	1.75	28	.29		
FC355-10	.50	.94	1250	5000	2.25	28	.40		
FC355-12	.63	1.08	750	3000	2.75	20	.46		
FC355-16	.88	1.24	400	1600	3.50	15	.50		
FC355-20	1.13	1.52	300	1250	4.50	15	.59		
FC355-24	1.38	1.75	250	1000	5.50	11	.69		
FC355-32	1.81	2.22	200	800	8.50	11	.93		

**Construction:** AQP elastomer tube, polyester inner braid and a single wire braid reinforcement, blue AQP elastomer cover.

**Application:** Air, gasoline, fuel, lubricating oils and coolants. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C). Air not to exceed 250 psi or +250°F (+121°C).

**For complete Agency Listings:** See pages 397-398.

HOSE

SPECIAL APPLICATION

# FC350

Engine & air brake  
FMVSS106



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	145
FC350-04	.19	.52	2000	8000	.75	28	.12	Sockets	73
FC350-05	.25	.58	1500	6000	1.00	28	.15	Accessories and Assembly Instructions see page 346.	
FC350-06	.31	.68	1500	6000	1.25	28	.20		
FC350-08	.41	.77	1250	5000	1.75	28	.22		
FC350-10	.50	.94	1250	5000	2.25	28	.32		
FC350-12	.63	1.08	750	3000	2.75	20	.39		
FC350-16	.88	1.23	400	1600	3.50	15	.38		
FC350-20	1.12	1.50	300	1200	4.50	15	.45		
FC350-24	1.38	1.75	250	1000	5.50	11	.54		

**Construction:** AQP elastomer tube, polyester inner braid and a single wire braid reinforcement; black polyester textile braided cover.

**Application:** Air, gasoline, fuel lubricating oils and coolants. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -55°F to +300°F (-49°C to +150°C). Air not to exceed +250°F (+121°C).

**For complete Agency Listings:** See pages 397-398.

# FC650

High temperature fuel & oil



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								CRIMP FITTINGS	
FC650-04	.19	.48	1000	4000	.75	28	.10	Contact Aeroquip for fitting information.	
FC650-06	.31	.63	1000	4000	1.25	28	.15	Accessories and Assembly Instructions see page 346.	
FC650-08	.41	.74	1000	4000	1.75	28	.19		
FC650-10	.50	.83	1000	4000	2.25	28	.23		
FC650-12	.63	.99	1000	4000	2.75	20	.28		

**Construction:** AQP elastomer tube, single wire braid reinforcement, black polyester braided cover.

**Application:** Diesel fuel, gasoline, fuel, lubricating oils, water, coolant and air. Not approved for air brake applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -55°F to +300°F (-49°C to +150°C). Air not to exceed +250°F (+121°C).

**For complete Agency Listings:** See pages 397-398.





**FC699**  
 High temperature fuel hose  
 AQP lightweight engine hose



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								<b>CRIMP FITTINGS</b>	
FC699-04	.25	.49	400	1600	2.50	28	.06	<i>Global</i>	
FC699-06	.38	.63	400	1600	3.00	28	.10	OTC	74
FC699-08	.50	.77	400	1600	4.00	28	.13	<i>Accessories and Assembly Instructions see page 346.</i>	
FC699-10	.63	.94	350	1400	5.00	18	.18		
FC699-12	.75	1.08	350	1400	7.00	18	.20		

**Construction:** AQP elastomer tube, single Kevlar reinforcement braid and textile braided cover.  
**Application:** Diesel fuel, gasoline, crude and lubricating oils.  
**Operating Temperature Range:** -40°F to +300°F (-40°C to +150°C). Air not to exceed +250°F (+121°C).  
**For complete Agency Listings:** See pages 397-398.

**FC321**  
 LPG UL listing MH6044



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
#								<b>REUSABLE FITTINGS</b>	145
FC321-04	.19	.52	350	1750	1.50		.11	<i>Sockets</i>	73
FC321-05	.25	.58	350	1750	1.75		.13	<i>Accessories and Assembly Instructions see page 346.</i>	
FC321-06	.31	.67	350	1750	2.00		.18		
FC321-08	.41	.77	350	1750	2.31		.21		
FC321-10	.50	.92	350	1750	2.75		.29		
FC321-12	.63	1.08	350	1750	3.25		.37		
FC321-16	.88	1.24	350	1750	3.69		.38		

**Construction:** Synthetic rubber tube, a textile inner braid, a stainless steel wire braid reinforcement and a synthetic rubber impregnated textile braid cover.  
**Application:** Designed for butane-propane applications on either mobile or stationary equipment. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).  
**For complete Agency Listings:** See pages 397-398.  
**WARNING:** LPG is a very hazardous liquid or gas and should be handled with maximum care to prevent leakage. Since the gas is heavier than air, it may flow along the ground if it escapes and cause an explosion or a fire. No leakage should ever be tolerated.

HOSE

SPECIAL APPLICATION

## CR170

Single stainless steel braid LPG hose  
CGA (Canadian Gas Association) Type III



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
CR170-04	.19	.52	350	12000	3.00		.16	Contact Aeroquip for fitting information	
CR170-06	.31	.67	350	9000	4.00		.22	<b>Accessories and Assembly Instructions see page 346.</b>	
CR170-08	.41	.77	350	8000	4.62		.26		

**Construction:** Nylon tube, single stainless steel braid reinforcement, perforated synthetic rubber cover.  
**Application:** LPG (propane) vehicle, alternative fuel conversion systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).  
**For complete Agency Listings:** See pages 397-398.

## FC414

Single wire braid  
Pressure washer hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b>	
FC414-06	.38	.68	5.00	3000	12000		.21	Global	
								TTC	74

**Construction:** Synthetic rubber tube, single wire braid reinforcement and synthetic rubber cover.  
**Application:** Pressure washer machines with working pressures up to 3000 psi. For more information on specific fluid applications and high temperature ratings, see pages 400-404.  
**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).  
**For complete Agency Listings:** See pages 397-398.

**WARNING: NOT FOR STEAM USE**

**Accessories and Assembly Instructions see page 346.**

## 2555

### Power steering



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	172
2555-6	.38	.76	1125	4500	4.00		.20	Sockets	73

**Construction:** Synthetic rubber tube, double textile braid reinforcement and synthetic rubber cover.

**Application:** Power steering applications. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

Accessories and Assembly Instructions see page 346.

## 1531/1531A

### Railroad air brake

### Exceeds AAR-M618



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	173
1531-10	.50	.94	300	1200	5.50		.38	Sockets	73
1531-12	.63	1.12	300	1200	6.50		.48	Accessories and Assembly Instructions see page 346.	
1531-16	.88	1.38	300	1200	7.38		.72		
1531-20	1.13	1.63	300	1200	9.50		.78		
1531A-24	1.38	1.88	300	1200	10.50		1.04		

**Construction:** Synthetic rubber tube, partial textile braid, wire reinforcement (1531-10 and 1531-12 have single wire braid; 1531-16, 1531-20 and 1531A-24 have double wire braid) and synthetic rubber cover.

**Application:** Locomotive air brake lines. For more information on specific fluid applications and high temperature ratings, see pages 400-404.


**Operating Temperature Range:** -65°F to +212°F (-54°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

**2550/2554**

Air brake

SAE J1402 FMVSS106



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	172
2550-6	.38	.75	225	900	1.75		.20	Sockets	73
2554-6	.38	.75	225	900	3.75		.18	Accessories and Assembly Instructions see page 346.	

**Construction:** Synthetic rubber tube, double textile braids and synthetic rubber cover.

**Application:** Tractor to trailer lines, axle chamber lines and tractor service lines. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** 2550: -40°F to +200°F (-40°C to +93°C). 2554: -65°F to +212°F (-54°C to 100°C), conforms to ordinance spec. MIL-H-3992B, Type 1, Class 1.

**For complete Agency Listings:** See pages 397-398.

**2570**

Air brake SAE J1402

FMVSS106



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	172
2570-6	.38	.75	225	900	1.75		.18	Sockets	73
2570-8	.50	.88	225	900	2.00		.23	Accessories and Assembly Instructions see page 346.	
2570-10‡	.62	1.06	225	900	2.25		.30		

**Construction:** Synthetic rubber tube, double textile braid and synthetic rubber cover.

**Application:** Tractor to trailer lines, axle chamber lines and tractor service lines. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

‡ Crimp Fittings only, contact Eaton Aeroquip.

# FC252

Silicone rubber (heater)



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
FC252-08	.50	.81	50	200	2.00		.18		
FC252-10	.63	.94	40	160	2.50		.19		
FC252-12	.75	1.06	40	160	3.00		.28		
FC252-16	1.00	1.34	35	140	4.00		.36		

FITTING REFERENCE	PAGE
<b>REUSABLE FITTINGS</b>	
<i>Clamps</i>	173
<i>Accessories and Assembly Instructions see page 346.</i>	

**Construction:** Silicone rubber tube, braided fiber reinforcement and silicone rubber cover.

**Application:** Heater hose for passenger cars and trucks; connecting lines from hot water heaters to coolant-circulating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +350°F (-54°C to +177°C).

**For complete Agency Listings:** See pages 397-398.

HOSE

SPECIAL APPLICATION

## FC352

Silicone rubber (coolant)



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
FC352-08	.50	.94	100	425			.17	<b>REUSABLE FITTINGS</b> <i>Clamps</i> 173 <i>Accessories and Assembly Instructions see page 346.</i>	
FC352-10	.63	1.06	100	425			.22		
FC352-12	.75	1.19	100	425			.27		
FC352-14	.88	1.32	100	425			.31		
FC352-16	1.00	1.44	90	375			.34		
FC352-18	1.12	1.56	90	375			.41		
FC352-20	1.25	1.69	85	350			.45		
FC352-22	1.38	1.82	85	350			.50		
FC352-24	1.50	1.94	85	350			.55		
FC352-26	1.63	2.06	80	325			.58		
FC352-28	1.75	2.19	80	325			.63		
FC352-32	2.00	2.44	75	300			.72		
FC352-36	2.25	2.69	75	300			.81		
FC352-38	2.38	2.82	60	250			.84		
FC352-40	2.50	2.94	60	250			.89		
FC352-44	2.75	3.19	50	200			.98		
FC352-48	3.00	3.44	50	200			1.06		
FC352-56	3.50	3.94	40	175			1.25		
FC352-64	4.00	4.44	35	150			1.44		

**Construction:** Silicone rubber tube, four spirals of nylon and silicone rubber cover.

**Application:** Coolant system service with liquid-cooled engines. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +350°F (-54°C to +177°C).

**For complete Agency Listings:** See pages 397-398.

## FC579

Jack Hose approved for 10,000 psi  
Static jacking applications



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
FC579-04	.25	.53	10000	20000	2.00		.22	CRIMP FITTINGS Global	

**Construction:** Synthetic rubber tube, double wire braid reinforcement and synthetic rubber cover.

**Application:** Hydraulic jacking system service with petroleum and water-base fluids. Meets the performance requirements of the Material Handling Institute Specification IJ100. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +212°F (-40°C to +100°C).

**For complete Agency Listings:** See pages 397-398.

FITTING REFERENCE	PAGE
CRIMP FITTINGS	
Global	
Skive Nipples	74
TTC	74
Sockets	72
Accessories and Assembly Instructions	see page 346.

## FC616

Jack Hose approved for 10,000 psi  
Static jacking applications



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
FC616-06	.38	.79	10000	20000	5.00		.47	CRIMP FITTINGS Global	

**Construction:** Synthetic rubber tube, four-wire spiral reinforcement and synthetic rubber cover.

**Application:** Hydraulic jacking system service with petroleum and water-base fluids. Meets the performance requirements of the Material Handling Institute Specification IJ100. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

FITTING REFERENCE	PAGE
CRIMP FITTINGS	
Global	
TTC12	74
Accessories and Assembly Instructions	see page 346.

## FC558

Refrigeration/air conditioning SAE J2064

Type B Class 1



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
FC558-10	.50	.92	500	2500	5.50	28	.33
FC558-12	.63	1.06	500	2500	6.50	28	.41
FC558-16	.88	1.24	500	2500	7.38	28	.47
FC558-20	1.12	1.51	500	2500	9.00	28	.57
FC558-24	1.38	1.75	500	2500	10.50	28	.69

**Construction:** Butyl rubber tube, single wire braid reinforcement and textile braid cover.

**Application:** Designed for applications using only refrigerant 134a. Not recommended for applications using Refrigerant 12 or R22. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

FITTING REFERENCE	PAGE
REUSABLE FITTINGS	145
Sockets	73
<i>Accessories and Assembly Instructions see page 346.</i>	

## FC802

Multi-Refrigerant hose

SAE J51 Type D



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service*	Weight Per Foot
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
FC802-04	.20	.52	500	2500	2.00	25*	.11
FC802-06	.33	.68	500	2500	2.50	25*	.16
FC802-08	.42	.77	500	2500	3.00	25*	.18
FC802-10	.52	.92	500	2500	3.50	25*	.29
FC802-12	.65	1.08	500	2500	4.50	25*	.35

**Construction:** Bromobutyl cover, polyamide-veneer tube, synthetic braid reinforcement, synthetic rubber backing layer.

**Application:** Transportation, refrigeration and air conditioning systems using Refrigerant 12, R-22, R-134a, R-502. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +250°F (-40°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

*\*All sizes of FC802 will withstand full negative pressure for charging purposes and are suitable for very short term service at full negative pressure.*

FITTING REFERENCE	PAGE
REUSABLE FITTINGS	145
Sockets	73
<i>Accessories and Assembly Instructions see page 346.</i>	



**1540****Refrigeration/air conditioning**

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service*	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
1540-4	.19	.50	350	1750	3.00	28	.12	<b>REUSABLE FITTINGS</b> Sockets <i>Accessories and Assembly Instructions see page 346.</i>	145
1540-6	.31	.67	350	1750	4.00	28	.18		73
1540-8	.41	.75	350	1750	4.62	28	.23		
1540-10	.50	.92	350	1750	5.50	28	.32		
1540-12	.63	1.06	350	1750	6.50	28	.45		
1540-16	.88	1.24	350	1750	7.38	28	.45		
1540-20	1.12	1.50	350	1750	9.00	28	.57		
1540-24	1.38	1.75	350	1750	10.50	28	.69		

**Construction:** Synthetic rubber tube, single wire braid reinforcement and black textile braided cover.

**Application:** Designed for applications using Refrigerant 12. Not recommended for applications using Freon 22 or R-502. See pages 400-404.

**Operating Temperature Range:** -20°F to +250°F (-29°C to +121°C).

**For complete Agency Listings:** See pages 397-398.

\*All sizes will withstand full negative pressure for charging purposes.

**FC555****Refrigeration/air conditioning  
Multi-refrigerant**

Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service*	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#									
FC555-12	.63	1.12	500	2500	2.50	29.5	.20	<b>CRIMP FITTINGS</b> Refer to Catalog JA466 <i>Accessories and Assembly Instructions see page 346.</i>	
FC555-16	.88	1.38	500	2500	3.00	29.5	.25		
FC555-20	1.12	1.65	500	2500	4.00	29.5	.33		

**Construction:** Corrugated nylon tube, stabilized synthetic braid reinforcement and abrasion-resistant polyester braided cover.

**Application:** Transportation refrigeration and air conditioning systems using R-134a, R-12, R-22 or R-502 (contact Eaton Aeroquip for additional refrigerants). See pages 400-404.

**Operating Temperature Range:** -22°F to +257°F (-30°C to +125°C).

**For complete Agency Listings:** See pages 397-398.

\*All sizes will withstand full negative pressure for charging purposes.

**GH134**

Refrigeration/air conditioning

SAE J2064 Type E Class 1, Multi-refrigerant



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service*	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b> Refer to Catalog JA466 <i>Accessories and Assembly Instructions see page 346.</i>	
GH134-6	.31	.58	500	2500	2.00	29.5	.09		
GH134-8	.41	.70	500	2500	2.50	29.5	.12		
GH134-10	.50	.78	500	2500	3.00	29.5	.15		
GH134-12	.63	.98	500	2500	4.00	29.5	.18		

**Construction:** Nylon veneer tube, stabilized synthetic braided reinforcement and chlorobutyl rubber cover.

**Application:** Transportation refrigeration and air conditioning systems using R-134a, R12, R22, R404 and R407. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +257°F (-40°C to +135°C).

**For complete Agency Listings:** See pages 397-398.

\*All sizes will withstand full negative pressure for charging purposes.

**FC505**

Refrigeration/air conditioning

SAE J2064 Type E Class 1, Multi-refrigerant



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service*	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>CRIMP FITTINGS</b> Refer to Catalog JA466 <i>Accessories and Assembly Instructions see page 346.</i>	
FC505-04	.20	.44	500	2500	1.50	29.5	.07		
FC505-06	.32	.59	500	2500	2.00	29.5	.10		
FC505-08	.42	.71	500	2500	2.50	29.5	.12		
FC505-10	.52	.79	500	2500	3.00	29.5	.14		
FC505-12	.64	.98	500	2500	4.00	29.5	.22		

**Construction:** Nylon veneer tube, stabilized synthetic braided reinforcement and chlorobutyl rubber cover.

**Application:** Transportation refrigeration and air conditioning systems using R-134a, R-12, R-22 or R-502 (contact Eaton Aeroquip for additional refrigerants). For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +275°F (-40°C to +135°C).

**For complete Agency Listings:** See pages 397-398.

\*All sizes will withstand full negative pressure for charging purposes.

# FC372

## Polyon™/Thermoplastic

### SAE 100R7



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE PAGE	
								SWAGE/CRIMP CRIMP FITTINGS	135
FC372-02	.13	.33	2500	10000	.50		.05	<i>Global</i>	
FC372-03	.19	.44	3000	12000	.75		.06	**Skive Nipples	74
FC372-04	.25	.53	2750	11000	1.25		.09	Sockets	72
FC372-05	.31	.59	2500	10000	1.75		.10	REUSABLE FITTINGS	153
FC372-06	.38	.66	2250	9000	2.00		.12	Sockets	73
FC372-08	.50	.83	2000	8000	3.00		.17		
FC372-10	.63	.94	1500	6000	4.00		.19		
FC372-12	.75	1.07	1250	5000	5.00		.22		
FC372-16	1.00	1.32	1000	4000	8.00		.28	Accessories and Assembly Instructions see page 346.	

**Construction:** Thermoplastic elastomer tube, single braid polyester reinforcement and a black perforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, pneumatic, fuel, and lubricating systems. For more information on specified fluid applications and high temperature ranges, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C) air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (-40°C to +93°C) for flexing applications. \*\*No skiving of cover required.

# FC373

## Polyon™/Thermoplastic

### SAE 100R7 Nonconductive



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE PAGE	
								SWAGE/CRIMP CRIMP FITTINGS	135
FC373-02	.13	.33	2500	10000	.50		.05	<i>Global</i>	
FC373-03	.19	.44	3000	12000	.75		.06	**Skive Nipples	74
FC373-04	.25	.53	2750	11000	1.25		.08	Sockets	72
FC373-05	.31	.59	2500	10000	1.75		.09	REUSABLE FITTINGS	153
FC373-06	.38	.66	2250	9000	2.00		.10	Sockets	73
FC373-08	.50	.83	2000	8000	3.00		.16		
FC373-12	.75	1.07	1250	5000	5.00		.22		
FC373-16	1.00	1.32	1000	4000	8.00		.27	Accessories and Assembly Instructions see page 346.	

**Construction:** Thermoplastic elastomer tube, single braid polyester reinforcement and an orange nonperforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404. For non-conductivity information see item 8 on page 408.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (-40°C to +93°C) for flexing applications.

\*\*Skiving not required.

# FC374

Polyon™/Thermoplastic  
SAE 100R8



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								SWAGE/CRIMP	135
FC374-03	.19	.40	5000	20000	1.50		.05	Accessories and Assembly Instructions see page 346.	
FC374-04	.25	.51	5000	20000	2.00		.08		
FC374-06	.38	.66	4000	16000	2.50		.12		
FC374-08	.50	.81	3500	14000	4.00		.16		
FC374-12	.75	1.08	2250	9000	8.00		.23		
FC374-16	1.00	1.32	2000	8000	10.00		.27		

**Construction:** Thermoplastic elastomer tube, single braid aramid reinforcement and a black perforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, pneumatic, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C), air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

† -40°F to +200°F (-40°C to +93°C) for flexing applications.

# FC375

Polyon™/Thermoplastic  
SAE 100R8 Nonconductive



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								SWAGE/CRIMP	135
FC375-03	.19	.41	5000	20000	1.50		.05	Accessories and Assembly Instructions see page 346.	
FC375-04	.25	.51	5000	20000	2.00		.07		
FC375-06	.38	.66	4000	16000	2.50		.11		
FC375-08	.50	.81	3500	14000	4.00		.14		
FC375-12	.75	1.06	2250	9000	8.00		.22		
FC375-16	1.00	1.37	2000	8000	10.00		.27		

**Construction:** Thermoplastic elastomer tube, single braid aramid reinforcement and an orange nonperforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404. For nonconductivity information, see item 8 page 408.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C).


**For complete Agency Listings:** See pages 397-398.

† -40°F to +200°F (-40°C to +93°C) for flexing applications.

# FC376

## Polyon™/Thermoplastic

### Ultra high pressure



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC376-03	.19	.50	10000‡	40000	1.50		.09	Contact Eaton Aeroquip for fitting information	
FC376-04	.25	.63	10000‡	35000	2.50		.13	<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** Thermoplastic elastomer tube, double braid aramid reinforcement and a black perforated polyurethane cover.

**Application:** High pressure hydraulic system service with petroleum, fire-resistant, and water-base fluids, pneumatic and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -40°F to +150°F (-40°C to +66°C).

**For complete Agency Listings:** See pages 397-398.

‡CAUTION: Applies only to hose that has suffered no damage, has been properly assembled with hose guards, and tested to required test pressure.

**WARNING:** The use of this hose in high pressure application requires the use of undamaged hose which has been properly assembled with hose guards and tested to the required pressure. Installations must not exceed the recommended minimum bend radius. The failure to follow these instructions may result in sudden hose failure with the potential for serious personal injury and property damage.

**CRIMP FITTINGS**  
Contact Eaton Aeroquip for fitting information  
**Accessories and Assembly Instructions see page 346.**

# FC377

## Polyon™/Thermoplastic

### Nonconductive, ultra high pressure



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
								<b>CRIMP FITTINGS</b>	
FC377-03	.19	.50	10000‡	40000	1.50		.08	Contact Eaton Aeroquip for fitting information	
FC377-04	.25	.63	10000‡	35000	2.50		.13	<b>Accessories and Assembly Instructions see page 346.</b>	

**Construction:** Thermoplastic elastomer tube, double braid aramid reinforcement and orange nonperforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 400-404. For nonconductivity information, see item 8 on page 408.

**Operating Temperature Range:** -40°F to +150°F (-40°C to +66°C).

**For complete Agency Listings:** See pages 397-398.

‡CAUTION: Applies only to hose that has suffered no damage, has been properly assembled with hose guards, and tested to required test pressure.

**WARNING:** The use of this hose in high pressure application requires the use of undamaged hose which has been properly assembled with hose guards and tested to the required pressure. Installations must not exceed the recommended minimum bend radius. The failure to follow these instructions may result in sudden hose failure with the potential for serious personal injury and property damage.

**CRIMP FITTINGS**  
Contact Eaton Aeroquip for fitting information  
**Accessories and Assembly Instructions see page 346.**

## FC690

### Polyon™/Thermoplastic

### Low temperature flexing SAE 100R7



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								<b>SWAGE</b> Accessories and Assembly Instructions see page 346.	135
FC690-04RL	.25	.53	2750	11000	1.25		.09		
FC690-06RL	.38	.66	2500	10000	2.50		.11		
FC690-08RL	.50	.84	2500	10000	3.50		.18		

**Construction:** Thermoplastic elastomer tube, double braid polyester reinforcement and low temperature black, perforated polyurethane cover.

**Application:** Hydraulic system service with petroleum, fire-resistant, and water-base fluids, pneumatic, fuel, and lubricating systems utilized in continuous low temperature flexing applications. For more information on specified fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F (-54°C to +93°C). Water not to exceed +150°F (+66°C), air not to exceed +160°F (+71°C). Sold in reel lengths only.

**For complete Agency Listings:** See pages 397-398.

## FC902

### Polyon™/Thermoplastic Twin-line

### SAE 100R7



Part Number	Number of Hoses	Hose I.D.	Polyon™ Hose Series	FITTING REFERENCE	PAGE
		INCHES			
FC902-00-Length Designation	2	0.19	FC372-03	<b>SWAGE/CRIMP</b> Swage	135
FC902-01-Length Designation	2	0.25	FC372-04		
FC902-02-Length Designation	2	0.31	FC372-05	Crimp** Skive Nipples Sockets	74 72
FC902-03-Length Designation	2	0.38	FC372-06		
FC902-04-Length Designation	2	0.50	FC372-08	<b>REUSABLE FITTINGS</b> Sockets	153 73
FC902-05-Length Designation	2	0.75	FC372-12		
FC902-06-Length Designation	2	1.00	FC372-16	Accessories and Assembly Instructions see page 346.	

**Construction:** Two Aeroquip SAE 100R7 thermoplastic hoses permanently joined.

**Application:** Hydraulic system service with petroleum, fire-resistant and water-base fluids, pneumatic, fuel, and lubricating systems. For more information on specified applications and high temperature ranges, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C) air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (40°C to +93°C) for flexing applications.

\*\*No skiving of cover needed.

# FC901

## Polyon™/Thermoplastic Twin-line SAE 100R7 Nonconductive



Part Number	Number of Hoses	Hose I.D.	Polyon™ Hose Series	FITTING REFERENCE	PAGE
		INCHES			
FC901-00-Length Designation	2	0.19	FC373-03	SWAGE/CRIMP Swage	135
FC901-01-Length Designation	2	0.25	FC373-04		
FC901-02-Length Designation	2	0.31	FC373-05	Crimp** Skive Nipples Sockets	74 72
FC901-03-Length Designation	2	0.38	FC373-06		
FC901-04-Length Designation	2	0.50	FC373-08	REUSABLE FITTINGS Sockets	153 73
FC901-05-Length Designation	2	0.75	FC373-12		
FC901-06-Length Designation	2	1.00	FC373-16		

**Construction:** Two Aeroquip SAE 100R7 Nonconductive thermoplastic hoses permanently joined.

**Application:** Hydraulic system service with petroleum, fire-resistant and water-base fluids, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404. For nonconductivity information see item 8 on page 408.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (-40°C to +93°C) for flexing applications.

\*\*No skiving of cover needed.

*Accessories and Assembly Instructions see page 346.*

# FC914

## Polyon™/Thermoplastic Twin-line SAE 100R8



Part Number	Number of Hoses	Hose I.D.	Polyon™ Hose Series	FITTING REFERENCE	PAGE
		INCHES			
FC914-00-Length Designation	2	0.19	FC374-03	SWAGE/CRIMP	135
FC914-01-Length Designation	2	0.25	FC374-04		
FC914-03-Length Designation	2	0.38	FC374-06	Accessories and Assembly Instructions see page 346.	
FC914-04-Length Designation	2	0.50	FC374-08		
FC914-05-Length Designation	2	0.75	FC374-12		
FC914-06-Length Designation	2	1.00	FC374-16		

**Construction:** Two Aeroquip SAE 100R8 thermoplastic hoses permanently joined.

**Application:** Hydraulic system service with petroleum, fire-resistant and water-base fluids, pneumatic, fuel, and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C), air not to exceed +160°F (+71°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (-40°C to +93°C) for flexing applications.

# FC916

## Polyon™/Thermoplastic Twin-line

### SAE 100R8 Nonconductive



Part Number	Number of Hoses	Hose I.D. INCHES	Polyon™ Hose Series	FITTING REFERENCE	PAGE
				SWAGE/CRIMP	135
FC916-00-Length Designation	2	0.19	FC375-03	<i>Accessories and Assembly Instructions see page 346.</i>	
FC916-01-Length Designation	2	0.25	FC375-04		
FC916-03-Length Designation	2	0.38	FC375-06		
FC916-04-Length Designation	2	0.50	FC375-08		
FC916-05-Length Designation	2	0.75	FC375-12		
FC916-06-Length Designation	2	1.00	FC375-16		

**Construction:** Two Aeroquip SAE 100R8 thermoplastic nonconductive hoses permanently joined.

**Application:** Hydraulic system service with petroleum, fire-resistant and water-base fluids, fuel and lubricating systems. For more information on specific fluid applications and high temperature ratings, see pages 400-404. For nonconductivity information, see item 8 page 408.

**Operating Temperature Range:** -65°F to +200°F† (-54°C to +93°C). Water not to exceed +150°F (+66°C).

**For complete Agency Listings:** See pages 397-398.

†-40°F to +200°F (-40°C to +93°C) for flexing applications.

**Important:** Cut lengths of twin-line hoses should be ordered as shown below by specifying the length in inches:

Example: FC902-00-00484

Hose Type  Cut Length (in inches) last digit is in 1/8ths of an inch 00484=48 1/8 inches

Aeroquip hose part #'s FC372, FC373, FC374, FC375, FC376 and FC377 can be permanently joined to form twin-line or multi-line hose designs. The above twin-line part #'s are the typical standard designs. If you would like to mate multiple pressure hoses in one design, please contact Eaton Aeroquip.

# FC701

## Sewer cleaning hose assemblies Gator™ hose



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
								SWAGE	139
FC701-12	.75	1.15	2500	6250	9.50		.27	<i>Accessories and Assembly Instructions see page 346.</i>	
FC701-16	1.01	1.41	2500	6250	12.00		.36		
FC701-20	1.26	1.79	2500	6250	12.00		.58		

**Construction:** Blue thermoplastic tube, single braid, polyester reinforcement and an orange ether-based polyurethane cover.

**Application:** High pressure sewer cleaning. For more information on specified applications and high temperature ranges, see pages 400-404.

**Operating Temperature Range:** -40°F to +150°F (-40°C to +66°C).

**For complete Agency Listings:** See pages 397-398.



# FC702

## Sewer cleaning hose assemblies Gator™ hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
#	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS	SWAGE	139
FC702-12	.75	1.19	3000	7500	9.50		.29	Accessories and Assembly Instructions see page 346.	
FC702-16	1.01	1.41	3000	7500	12.00		.36		

**Construction:** Blue thermoplastic elastomer tube, single braid, high strength textile reinforcement and a blue ether-based polyurethane cover.


**Application:** High pressure sewer cleaning. For more information on specific applications and high temperature ranges, see pages 400-404.

**Operating Temperature Range:** -40°F to +150°F (-40°C to +66°C).

**For complete Agency Listings:** See pages 397-398.

# FC363

## Convuluted PTFE hose Nonconductive tube



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Minimum Kink Radius	Vacuum Service	FITTING REFERENCE	PAGE
#	INCHES	INCHES	PSI	PSI	INCHES	INCHES	INCH/Hg	CRIMP FITTINGS	
FC363-08	.54	.74	1250†	5000	2.88	1.00	28	Crimp	142
FC363-12	.81	1.06	1100†	4400	3.75	2.00	28	Sockets	72
FC363-16	1.00	1.28	1000†	4000	5.00	2.50	24	Accessories and Assembly Instructions see page 346.	
FC363-20	1.24	1.53	1000†	4000	6.25	3.50	20		
FC363-24	1.52	1.81	750†	3000	7.50	4.50	12		
FC363-32	2.00	2.31	500†	2000	10.00	6.00	5		

**Construction:** Convuluted PTFE tube with stainless steel single wire braid cover.

**Application:** Chemical, food, water and waste handling, and various transfer applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +400°F (-54°C to +204°C).

**For complete Agency Listings:** See pages 397-398.

†Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements, contact Eaton Aeroquip.

HOSE

SPECIAL APPLICATION

## FC364

### Convuluted PTFE hose Conductive



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum† Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Minimum Kink Radius INCHES	Vacuum Service INCH/Hg	FITTING REFERENCE	PAGE
#								<b>CRIMP FITTINGS</b>	
FC364-08	.54	.74	1250†	5000	2.88	1.00	28	Crimp	142
FC364-12	.81	1.06	1100†	4400	3.75	2.00	28	Sockets	72
FC364-16	1.00	1.27	1000†	4000	5.00	2.50	24	<i>Accessories and Assembly Instructions see page 346.</i>	
FC364-20	1.24	1.53	1000†	4000	6.25	3.50	20		
FC364-24	1.52	1.81	750†	3000	7.50	4.50	12		
FC364-32	2.00	2.31	500†	2000	10.00	6.00	5		
FC364-40	2.53	2.90	100	400	12.50	8.00	5		
FC364-48	3.04	3.48	100	400	15.00				

**Construction:** Convuluted conductive PTFE tube with stainless steel wire braid cover.

**Application:** Steam lines and fuel transfer applications where static dissipation is required. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.


**Operating Temperature Range:** -65°F to +400°F (-54°C to +204°C).

**For complete Agency Listings:** See pages 397-398.

†Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements, contact Eaton Aeroquip.

## FC563

### Convuluted PTFE hose Nonconductive tube



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum† Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Minimum Kink Radius INCH/Hg	Vacuum Service INCH/Hg	FITTING REFERENCE	PAGE
#								<b>CRIMP FITTINGS</b>	
FC563-08	.54	.74	1250	5000	2.88	1.00	28	Crimp	142
FC563-12	.81	1.06	1100	4400	3.75	2.00	28	Sockets	72
FC563-16	1.00	1.28	1000	4000	5.00	2.50	24	<i>Accessories and Assembly Instructions see page 346.</i>	
FC563-20	1.24	1.53	1000	4000	6.25	3.50	20		
FC563-24	1.52	1.81	750	3000	7.50	4.50	10		
FC563-32	2.00	2.31	500	2000	10.00	6.00	7		

**Construction:** Convuluted PTFE tube with stainless steel single wire braid reinforcement and integral black polyester overbraid cover.

**Application:** Chemical transfer and various chemical processing applications. Not recommended for steam or steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +300°F (-54°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

# FC186

## PTFE hose



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE PAGE	
								INCHES	INCHES
#								<b>CRIMP FITTINGS</b>	
FC186-04	.19	.30	1000	6000	2.00	28	.06	Crimp	140
FC186-05	.26	.37	1000	6000	3.00	28	.07	Sockets	72
FC186-06	.32	.43	1000	6000	4.00	28‡	.08	<b>REUSABLE FITTINGS</b>	
FC186-08	.42	.54	750	4500	5.25	28‡	.10	Sockets	73
FC186-10	.51	.63	600	4000	6.50	28‡	.14	<i>Accessories and Assembly Instructions see page 346.</i>	
FC186-12	.64	.76	600	4000	7.75	28‡	.16		

**Construction:** Extruded PTFE tube with stainless steel single wire braid.

**Application:** Hot air, steam, compressor discharge and most chemical applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +400°F (-54°C to +204°C).

**For complete Agency Listings:** See pages 397-398.

† Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.

‡ Maximum negative pressure for -.06 and larger are suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required for -.06 and larger hoses, the use of an internal support coil is recommended. Use of an internal support coil in -.06 and larger PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.

# 2807

## PTFE hose

### SAE 100R14A



Part Number	Hose I.D.	Hose O.D.	Maximum Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE PAGE	
								INCHES	INCHES
#								<b>CRIMP FITTINGS</b>	
2807-3	.14	.25	3000	12000	1.50	28	.04	Crimp	140
2807-4	.19	.30	3000	12000	2.00	28	.06	Sockets	72
2807-5	.26	.37	3000	12000	3.00	28	.08	<b>REUSABLE FITTINGS</b>	
2807-6	.32	.43	2500	10000	4.00	28‡	.10	Sockets	73
2807-8	.42	.54	2000	8000	5.25	28‡	.12	<i>Accessories and Assembly Instructions see page 346.</i>	
2807-10	.51	.63	1500	6000	6.50	28‡	.16		
2807-12	.64	.76	1200	4800	7.75	28‡	.18		
2807-16	.88	1.03	1000	4000	9.00	12‡	.26		
2807-20	1.12	1.29	625	2500	16.00	12‡	.34		

**Construction:** Extruded PTFE tube with stainless steel single wire braid.

**Application:** Hot air, steam, compressor discharge and most chemical applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -100°F to +500°F (-73°C to +260°C).

**For complete Agency Listings:** See pages 397-398.

† Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.

‡ Maximum negative pressure for -.06 and larger are suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required for -.06 and larger hoses, the use of an internal support coil is recommended. Use of an internal support coil in -.06 and larger PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.

## FC645

### PTFE hose

#### Conductive SAE 100R14B performance



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
								<b>CRIMP FITTINGS</b>	
FC645-06	.32	.51	2500	10000	4.00	28‡	.10	Contact Aeroquip for Fitting Information, Factory Crimp Only	

**Construction:** Conductive extruded black PTFE tube with stainless steel single black wire braid abrasion resistant engine hose.

**Application:** Steam, compressor discharge and most chemical applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -100°F to +300°F (-73°C to +150°C).

**For complete Agency Listings:** See pages 397-398.

†Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.

‡Maximum negative pressure is suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required, the use of an internal support coil is recommended. Use of an internal support coil in -06 PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.

**CRIMP FITTINGS**  
Contact Aeroquip for Fitting Information, Factory Crimp Only  
**Accessories and Assembly Instructions see page 346.**

## FC465

### PTFE hose

#### Conductive SAE 100R14B



Part Number	Hose I.D. INCHES	Hose O.D. INCHES	Maximum Operating Pressure PSI	Minimum Burst Pressure PSI	Minimum Bend Radius INCHES	Vacuum Service INCH/Hg	Weight Per Foot POUNDS	FITTING REFERENCE	PAGE
								<b>CRIMP FITTINGS</b>	
FC465-03	.14	.25	3000	12000	1.50	28	.04	Crimp	140
FC465-04	.19	.30	3000	12000	2.00	28	.06	Sockets	72
FC465-05	.26	.37	3000	12000	3.00	28	.08	<b>REUSABLE FITTINGS</b>	174
FC465-06	.32	.43	2500	10000	4.00	28‡	.10	Sockets	73
FC465-08	.42	.54	2000	8000	5.25	28‡	.12	<b>Accessories and Assembly Instructions see page 346.</b>	
FC465-10	.51	.63	1500	6000	6.50	28‡	.16		
FC465-12	.64	.76	1200	4800	7.75	28‡	.18		
FC465-16	.88	1.03	1000	4000	9.00	12‡	.26		
FC465-20	1.12	1.29	625	2500	16.00	12‡	.34		

**Construction:** Conductive extruded black PTFE tube with stainless steel single wire braid.

**Application:** Steam, compressor discharge and most chemical applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -100°F to +500°F (-73°C to +260°C).

**For complete Agency Listings:** See pages 397-398.

†Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.

‡Maximum negative pressure for -06 and larger are suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required for -06 and larger hoses, the use of an internal support coil is recommended. Use of an internal support coil in -06 and larger PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.

**CRIMP FITTINGS**  
Crimp 140  
Sockets 72  
**REUSABLE FITTINGS** 174  
Sockets 73  
**Accessories and Assembly Instructions see page 346.**

## 2808

### PTFE hose



Part Number	Hose I.D.	Hose O.D.	Maximum† Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								REUSABLE FITTINGS	175
2808-8	.42	.58	2750	11000	4.62	28‡	.20	Sockets	73
2808-10	.51	.68	2500	10000	5.50	28‡	.26	Accessories and Assembly Instructions see page 346.	
2808-12	.64	.81	1750	7000	6.50	20‡	.30		
2808-16	.88	1.09	1500	6000	7.38	15‡	.44		
2808-20	1.12	1.35	1125	4500	11.00	15‡	.57		
2808-24	1.38	1.62	800	3200	14.00	15‡	.70		

**Construction:** Extruded PTFE tube with double stainless steel braids.

**Application:** Hot air, steam and most chemical applications. Not recommended for steam-cold water cycling. For more information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -100°F to +500°F (-73°C to +260°C).

**For complete Agency Listings:** See pages 397-398.

† Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.  
‡ Maximum negative pressure for -.08 and larger are suitable for hose which has suffered no external damage or kinking. If greater negative pressures are required for -.08 and larger hoses, the use of an internal support coil is recommended. Use of an internal support coil in -.08 and larger PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.

## FC469

### PTFE hose

### Conductive



Part Number	Hose I.D.	Hose O.D.	Maximum† Operating Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Service	Weight Per Foot	FITTING REFERENCE	PAGE
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS		
#								CRIMP FITTINGS	
FC469-06	.30	.48	4000	16000	2.50	28‡	.17	Contact Aeroquip for fitting information.	
FC469-08	.39	.61	4000	16000	2.88	28‡	.24	Accessories and Assembly Instructions see page 346.	
FC469-10	.49	.72	3500	14000	3.25	28‡	.29		

**Construction:** Conductive extruded PTFE tube with stainless steel single wire braid.

**Application:** High pressure chemical and fluid transfer. For information on specific fluid applications and high temperature ratings, see pages 400-404.

**Operating Temperature Range:** -65°F to +400°F (-54°C to +204°C).

**For complete Agency Listings:** See pages 397-398.

† Steam 200 psi at +388°F max. Engineering information is available for specific critical temperature requirements. Contact Eaton Aeroquip.  
‡ Use of an internal support coil in -.06 and larger PTFE hose is recommended for tube support where extended or continuous service at high temperature together with low or negative pressure is expected.